

## **Access Point MIKROTIK IEEE 802.11b IEEE 802.11g IEEE 802.11n 1xRJ45 RBCAPL-2ND**



Model: RBCAPL-2ND

Manufacturer: MIKROTIK

EAN: 4752224003423

Product Code: 194764

## **R640**

The cAP lite is a tiny access point device, perfect for public locations and hospitality businesses like hotels, airports, shopping malls etc. Included with the product are two different casings, which can easily be swapped out, or, if you really like to fit the design with the environment, we are providing 3D printer friendly design files.

The cAP lite supports 802.11b/g/n and can be powered by power over ethernet. It's a perfect companion for the MikroTik CAPsMAN (controlled AP system manager), allowing you to control all your AP devices from one central location. The cAP lite can also be used as a stand alone access point with the full potential of RouterOS.

**Summary: Mikrotik cAP lite. 2.4 GHz, Maximum data transfer rate: 54 Mbit/s, Ethernet LAN data**

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

rates: 10,100 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 4 W | Vendor Homepage: <https://mikrotik.com/product/RBcAPL-2nD-307#fndtn-gallery> | 2.4 GHz: Yes | 5 GHz: No | Ethernet LAN data rates: 10/100 | Maximum data transfer rate: 54 | Networking standards: IEEE 802.11b/IEEE 802.11g/IEEE 802.11n/IEEE 802.3af/IEEE 802.3at | Receiver sensitivity: -96, -89, -93, -74, -71 | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 1 | USB connector type: Micro-USB | AC input voltage: 10 - 60 | Output voltage: 24 | Power consumption (max): 4 | Power over Ethernet (PoE): Yes | Internal: No | Placement: Ceiling,Wall | Product colour: White | Reset button: Yes | Antenna gain level (max): 1.5 | Antenna type: Internal | Built-in processor: Yes | Flash memory: 16 | Internal memory: 64 | Operating system installed: RouterOS | Depth: 20 | Height: 88 | Width: 52 | Operating temperature (T-T): -40 - 70 | Harmonized System (HS) code: 85176990 | Model name: cAP lite // RBcAPL-2nD | Units per Pallet: 500 | Units per Shipping Box: 20 | Unit Calculated Volume: 0.0009555 | Unit Calculated Weight: 0.231

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950