

Switch TP-LINK LS106LP PoE ports 4 LS106LP



Model: LS106LP

Manufacturer: TP-LINK

EAN: 4895252504606

Product Code: 194798

R604

- 41 W PoE Budget: Four 10/100 Mbps 802.3af-compliant PoE ports easily connect and power fixed devices like IP cameras, access points, and IP phones via a single cable. Up to 15.4 W PoE output is supported by each PoE port.*
- Up to 250 m PoE Transmission: With Extend Mode, PoE transmission distance reaches up to 250m, perfect for surveillance camera deployment in large areas.**
- PoE Auto Recovery: Automatically reboots your dropped or unresponsive PoE-powered devices.
- Plug and Play: Simply plug and play for instant connectivity with no configuration required.
- Silent Operation: Fanless design reduces power consumption and ensures silent operation, ideal for noise-sensitive homes or businesses.
- Reliable Hardware Design: Durable metal casing and desktop/wall-mounting design are well-suited for different environments.

Summary: TP-Link LiteWave LS106LP. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 6. MAC address table: 2000 entries, Switching capacity: 1.2 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3i, IEEE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

802.3u, IEEE 802.3x. DC input voltage: 53.5 V. Power over Ethernet (PoE). Wall mountable | Vendor Homepage: <https://www.tp-link.com/za/business-networking/soho-switch-poe/lS106lp/#overview> | Quality of Service (QoS) support: Yes | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 6 | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Cable types supported: Cat3/Cat4/Cat5/Cat5e | Copper ethernet cabling technology: 100BASE-TX/10BASE-T | Flow control support: Yes | Networking standards: IEEE 802.3af/IEEE 802.3i/IEEE 802.3u/IEEE 802.3x | Forwarding rate: 0.8928 | Jumbo frames support: Yes | MAC address table: 2000 | Store-and-forward: Yes | Switching capacity: 1.2 | LED indicators: Yes | Number of fans: 0 | Product colour: Black | Wall mountable: Yes | Fanless: Yes | AC input frequency: 50 | AC input voltage: 220 | DC input voltage: 53.5 | Input current: 0.81 | Power consumption (max): 47.76 | Power source: DC/PoE | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 4 | Power over Ethernet (PoE) power per port: 15.4 | Heat dissipation: 162.38 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 101 | Height: 25 | Width: 158 | User guide: Yes | Package type: Box | Certification: CE, FCC, RoHS | Model name: LS106LP | Units per Shipping Box: 1 | Unit Calculated Volume: 0.002437 | Unit Calculated Weight: 0.6

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950