

## NET SWITCH MODULE SFP 1000B- BX/SM321B TP- LINK



Model: SM321B

Manufacturer: TP-LINK

EAN: 6935364030520

Product Code: 194854

## R465

### Spotlight:

- WDM Bi-Directional SFP Module
- Supports WDM Bi-Directional technology, using a single strand of fiber, cost saving

TP-LINK's TL-SM321B adopts the latest standard 1000Base-BX, transmission over a single strand of fiber, with one different wavelength going in each direction. You can extend the network distance up to 10Km with TP-LINK's Routers, Switches, Media Converters to provide high speed and stability.

### Features

- Supports WDM Bi-Directional technology, using a single strand of fiber
- TX: 1310nm / RX: 1550nm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- Internal +3.3V Power Supply
- In pairs with TL-SM321A
- Plug-and-Play
- Suitable: MC220L, TL-R4199G/4299G, TL-SG3109, TL-SL3428/3452, TL-SG2109WEB/2216WEB/2224WEB, TL-SL2210WEB/2218WEB/2428WEB/2452WEB, TL-SL1351 and the other equivalent devices

Summary: TP-Link 1000Base-BX WDM Bi-Directional SFP Module. SFP transceiver type: Fiber optic, Maximum data transfer rate: 1250 Mbit/s, Interface type: SFP. Input voltage: 3.3 V. Certification: FCC, CE. Width: 55.4 mm, Depth: 12.9 mm, Height: 12.9 mm. Package width: 81.5 mm, Package depth: 122.5 mm, Package height: 38.5 mm | Vendor Homepage: <https://www.tp-link.com/products/productDetails.asp?class=&content=fea&pmodel=TL-SM321B> | Fiber cable diameters supported (core/cladding): 9/125 | Interface type: SFP | Maximum data transfer rate: 1250 | Maximum transfer distance: 10000 | Networking standards: IEEE 802.3z | Rx wavelength (max): 1310 | SFP transceiver type: Fiber optic | Single-mode fiber (SMF) supported: Yes | Tx wavelength (max): 1550 | Plug and Play: Yes | Input voltage: 3.3 | Certification: FCC, CE | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 70 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 80 | Depth: 12.9 | Height: 12.9 | Width: 55.4 | Package depth: 122.5 | Package height: 38.5 | Package weight: 60 | Package width: 81.5 | Harmonized System (HS) code: 85369010 | Model: TP-LINK TL-SM321B V3 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.000336 | Unit Calculated Weight: 0.06

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950