

Switch DAHUA PFS3008-8GT-L- V2 Type L2 DH- PFS3008-8GT-L- V2



Model: DH-PFS3008-8GT-L-V2

Manufacturer: DAHUA

EAN: 6923172582058

Product Code: 194863

R440

The Device is a layer-2 commercial switch. It has a high-performance switching engine and a large buffer memory to ensure smooth video stream transmission. With a plastic and fanless design, the device

provides a more cost-effective option for customers. The Device is an unmanaged switch, so it does not need to be configured through web interface, which simplifies installation

Robust Design

Built to last, the architecture of the switch makes it highly reliable, operating with high-efficiency non-stop.

Plug and Play

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Hassle-free, it does not require any configuration. Simply use after it is powered on.

Optimized Performance

All ports can transmit streams at high speeds without delay.

Easy Installation

Both desktop and wall mount installation are supported, making it suitable for a wide variety of scenarios.

- Supports eight 10/100/1000 Mbps adaptive ports
- Small and light, it is easy to carry and has multiple chips embedded in it
- Easy to operate

Summary: Dahua Technology PFS3008-8GT-L. Switch type: Unmanaged, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. MAC address table: 2000 entries, Switching capacity: 16 Gbit/s. DC input voltage: 5 V | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Transmission/IT-Channel-Products/SOHO-Switch/PFS3008-8GT-L> | Switch layer: L2 | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 8 | 10G support: No | Copper ethernet cabling technology: 1000BASE-T/100BASE-T/10BASE-T | Forwarding rate: 11.904 | MAC address table: 2000 | Packet buffer memory: 1.5 | Switching capacity: 16 | Housing material: Plastic | Product colour: White | Rack mounting: No | Fanless: Yes | Mean time between failures (MTBF): 5051758.14 | Plug and Play: Yes | DC input voltage: 5 | Input current: 1 | Power consumption (max): 3 | Power source: DC | Power supply included: Yes | Power over Ethernet (PoE): No | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): 0 - 45 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 70 | Depth: 132.9 | Height: 24 | Weight: 160 | Width: 62.4 | Package depth: 136 | Package height: 153 | Package weight: 290 | Package width: 55 | Sustainability compliance: Yes | Compliance certificates: CE/Federal Communications Commission (FCC) | Model name: PFS3008-8GT-L-V2 | Units per Pallet: 0 | Units per Shipping Box: 30 | Unit Calculated Volume: 0.001478 | Unit Calculated Weight: 0.27

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950