

Cudy P5 wireless router Gigabit Ethernet Dual-band (2.4 GHz 5 GHz) 5G Black



Model: P5_EU

Manufacturer: CUDY

EAN: 6971690792282

Product Code: 200064

R5,292

VPN support: PPTP/L2TP/OpenVPN/WireGuard/IPsec/Zerotier | MAC address filtering: Yes | Product colour: Black | MIMO: Yes | Network address translation (NAT): Yes | DC-in jack: Yes | Filtering: Yes | Processor cores: 2 | Firewall: Yes | Output voltage: 12 V | Universal Plug and Play (UPnP): Yes | WAN connection type: RJ-45 | External power adapter: Yes | Processor frequency: 1000 MHz | Antennas quantity: 6 | Cabling technology: 10/100/1000Base-T(X) | SIM card slot: Yes | Ethernet WAN: Yes | IP address filtering: Yes | Detachable antenna(s): Yes | Short Message Service (SMS): Yes | WLAN data transfer rate (first band): 574 Mbit/s | 3G standards: WCDMA | Package height: 90 mm | Flash memory: 128 MB | Port forwarding: Yes | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Port triggering: Yes | Processor manufacturer: Qualcomm | Ethernet LAN interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | Package width: 265 mm | DHCP server: Yes | WPS push button: Yes | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Power source type: AC | Browser supported:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Firefox 12.0, Chrome 20.0, Safari 4.0 | Linux operating systems supported: Yes | WLAN data transfer rate (max): 2402 Mbit/s | Operating temperature (T-T): 0 - 45 °C | Ethernet LAN (RJ-45) ports: 4 | DHCP client: Yes | Mac compatibility: Yes | 4G standard: LTE-FDD | SIM card type: NanoSIM | Dual SIM support: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Indication light: Yes | Height: 48.2 mm | Operating relative humidity (H-H): 5 - 95% | Windows operating systems supported: Windows NT | WLAN data transfer rate (second band): 2402 Mbit/s | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 7 | Windows operating systems supported: Windows 2000 | Cables included: LAN (RJ-45) | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Product type: Tabletop router | Windows operating systems supported: Windows 98SE | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Antenna included: Yes | 3G/4G USB modem compatibility: Yes | Mobile network generation: 5G | Ethernet LAN: Yes | Windows operating systems supported: Windows 10 | Depth: 253 mm | Ethernet LAN data rates: 1000 Mbit/s | DSL WAN: No | Width: 152.5 mm | Wi-Fi standards: 802.11g | Built-in processor: Yes | Security algorithms: TTLS | Wi-Fi standards: 802.11b | Mac operating systems supported: MacOS | AC input voltage: 90 - 260 V | Output current: 2.5 A | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Internal memory: 256 MB | 5G standard: Sub6 SA/NSA | Package depth: 415 mm | Quick installation guide: Yes | Internal memory type: DDR3 | Package type: Box | DMZ support: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 5G bands supported: 6000 MHz | Antenna design: External | AC adapter included: Yes | VPN server: PPTP/L2TP/OpenVPN/WireGuard/IPsec/Zerotier | USB port: No | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to water or moisture. | Warnings: Do not expose the device to extreme temperatures.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950