

Cudy Gigabit Multi-WAN VPN Router wired router Fast Ethernet, Gigabit Ethernet Grey



Model: R700

Manufacturer: CUDY

EAN: 6971690792985

Product Code: 200065

R905

Height: 28 mm | DHCP server: Yes | Flash memory: 16 MB | Ethernet interface type: Gigabit Ethernet | Ethernet interface type: Fast Ethernet | Policy-based routing: Yes | DoS attack prevention: Yes | URL filtering: Yes | DSL WAN: No | 3G/4G USB modem compatibility: No | Firewall: Yes | Housing material: Metal | Static route: Yes | System event log: Yes | IP address filtering: Yes | Supported network protocols: /IP, DHCP, ICMP, NAT, PPPoE, HTTP, DNS, IPSec, PPTP, L2TP, OpenVPN, WireGuard, Zerotier | Universal Plug and Play (UPnP): Yes | Internal memory: 128 MB | Sustainability compliance: Yes | Concurrent connections: 15360 | SIM card slot: No | DMZ support: Yes | WAN/Ethernet LAN ports quantity: 3 | SFP WAN: No | WAN ports quantity: 1 | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE | Warnings: Do not

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to water or moisture. | Warnings: Do not expose the device to extreme temperatures. | Product colour: Grey | Connectivity technology: Wired | Web-based management: Yes | MAC address filtering: Yes | Ethernet LAN (RJ-45) ports: 4 | Operating temperature (T-T): 0 - 40 °C | Depth: 85 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Quick installation guide: Yes | Cables included: LAN (RJ-45) | LED indicators: Activity | LED indicators: System | Operating relative humidity (H-H): 10 - 90% | Reset button: Yes | LED indicators: Link | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Security algorithms: SHA-1 | LED indicators: Power | LED indicators: WAN | Security algorithms: SHA-2 | Security algorithms: SHA-512 | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | AC adapter included: Yes | Security algorithms: 192-bit AES | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 1000 Mbit/s | Security algorithms: 3DES | Internal memory type: DRAM | Security algorithms: 128-bit AES | Ethernet WAN: Yes | Networking standards: IEEE 802.3u | Security algorithms: 256-bit AES | Width: 119 mm | Cabling technology: 10/100/1000Base-T(X) | Storage relative humidity (H-H): 5 - 90% | Ethernet LAN data rates: 10

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950