

Cudy FS1010PG network switch Fast Ethernet (10/100) Power over Ethernet (PoE) Black



Model: FS1010PG

Manufacturer: CUDY

EAN: 6971690791254

Product Code: 200082

R684

Product colour: Black | Networking standards: IEEE 802.3x | AC input voltage: 100 - 240 V |
Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | AC input frequency:
50/60 Hz | Networking standards: IEEE 802.3at | Ethernet LAN data rates: 10,100 Mbit/s | Warnings:
Do not open the case or try to repair it yourself. | Warnings: The product is not suitable for disposal
in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance
with local regulations. | Warnings: Ensure the unit is adequately ventilated during operation. | Plug
and Play: Yes | Fanless: Yes | Cables included: AC | Surge protection voltage: 4 kV | Power
consumption (max): 120 W | Weight: 636 g | Power connector: AC-in jack | Power over Ethernet plus
(PoE+) ports quantity: 1 | Operating relative humidity (H-H): 10 - 90% | Height: 44 mm | Package
weight: 1.04 kg | Bandwidth: 2 Gbit/s | Power over Ethernet (PoE) ports quantity: 8 | Full duplex: Yes |
Width: 220 mm | Forwarding rate: 1.48 Mpps | Power supply included: Yes | Power source: AC | Cable

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or
typographical errors. We recommend checking the current information before purchasing.

types supported: Cat4 | LED indicators: PoE | Power over Ethernet (PoE): Yes | Cable types supported: Cat3 | Package width: 249 mm | Warranty period: 1 year(s) | Store-and-forward: Yes | Power consumption (typical): 5 W | Depth: 150 mm | Basic switching RJ-45 Ethernet ports quantity: 8 | VLAN support: Yes | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Copper ethernet cabling technology: 10BASE-T | Surge protection: Yes | Cable types supported: Cat5 | Packet buffer memory: 0.25 MB | Cloud-managed: No | Copper ethernet cabling technology: 100BASE-TX | Cable types supported: Cat5e | Housing material: Metal | MAC address table: 8000 entries | Power over Ethernet (PoE) power per port: 30 W | Flow control support: Yes | Package depth: 207 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: No | Package height: 60 mm | Jumbo frames support: Yes | Jumbo frames: 1528 | Products per shipping (inner) case: 16 pc(s) | LED indicators: Link | Operating temperature (T-T): 0 - 40 °C | Storage relative humidity (H-H): 5 - 90% | Total Power over Ethernet (PoE) budget: 120 W | Uplink ports quantity: 2 | Half duplex: Yes | LED indicators: Power | LED indicators: Activity | Mean time between failures (MTBF): 50000 h

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950