

## **Cudy GS108 network switch Gigabit Ethernet (10/100/1000) Black**



Model: GS108

Manufacturer: CUDY

EAN: 6971690790554

Product Code: 200085

## **R481**

Weight: 300 g | Mean time between failures (MTBF): 100000 h | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Power source: AC/DC | Cable types supported: Cat3 | Cable types supported: Cat5 | Cable types supported: Cat5e | Store-and-forward: Yes | Operating altitude: 0 - 3048 m | Cable types supported: Cat8 | Networking standards: IEEE 802.3x | MAC address auto-aging supported: Yes | Package width: 175 mm | MAC address auto-learning supported: Yes | Jumbo frames: 2000 | LED indicators: Power | LED indicators: Loop | Operating temperature (T-T): -10 - 50 °C | Package type: Box | Products per master (outer) case: 40 pc(s) | AC input voltage: 100 - 240 V | LED indicators: Link | Jumbo frames support: Yes | Copper ethernet cabling technology: 10BASE-T | Auto-negotiation: Yes | Auto MDI/MDI-X: Yes | Cable types supported: Cat6+ | Copper ethernet cabling technology: 100BASE-TX | DC input voltage: 5 V | Cable types supported: Cat7 | Cable types supported: Cat6 | Cable types supported: Cat8.1 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Package weight: 500 g | Depth: 77 mm | Basic switching RJ-45 Ethernet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

ports quantity: 8 | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Quick start guide: Yes | Networking standards: IEEE 802.3u | Cable types supported: Cat6a | Switching capacity: 16 Gbit/s | Master (outer) case width: 505 mm | Cable types supported: Cat6e | Cable types supported: Cat7e | Package height: 63 mm | Cables included: DC | Warnings: Do not open the case or try to repair it yourself. | Packet buffer memory: 2.5 MB | Storage relative humidity (H-H): 5 - 90% | Ethernet LAN data rates: 10,100,1000 Mbit/s | MAC address table: 1000 entries | Height: 25 mm | Storage temperature (T-T): -40 - 70 °C | Product colour: Black | Master (outer) case gross weight: 21 kg | Flow control support: Yes | Full duplex: Yes | VLAN support: Yes | Copper ethernet cabling technology: 1000BASE-TX | Package depth: 120 mm | Master (outer) case length: 320 mm | Cable types supported: Cat4 | Power over Ethernet (PoE): No | Throughput: 11.9 Mpps | Width: 137 mm | Rack mounting: No | Half duplex: Yes | Master (outer) case height: 400 mm | Power supply included: Yes | Operating relative humidity (H-H): 10 - 90%

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950