

## **Cudy GS1005P network switch Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey**



Model: GS1005P

Manufacturer: CUDY

EAN: 6971690790998

Product Code: 200086

## **R867**

Networking standards: IEEE 802.3af | Housing material: Metal | Operating temperature (T-T): 0 - 40 °C | Power source: AC/DC | User guide: Yes | Storage temperature (T-T): -40 - 70 °C | Total Power over Ethernet (PoE) budget: 60 W | Product colour: Grey | Switching capacity: 10 Gbit/s | Power over Ethernet plus (PoE+) ports quantity: 1 | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Plug and Play: Yes | Cables included: DC | Height: 28 mm | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Basic switching RJ-45 Ethernet ports quantity: 5 | LED indicators: Activity | LED indicators: PoE | Package type: Box | LED indicators: Link | Networking standards: IEEE 802.3u | Flow control support: Yes | Power supply included: Yes | Operating relative

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

humidity (H-H): 0 - 90% | Rack mounting: Yes | Power over Ethernet (PoE): Yes | Width: 119 mm | Power consumption (typical): 5 W | Cables included: AC | LED indicators: Power | Ethernet LAN data rates: 10,100,1000 Mbit/s | MAC address table: 2000 entries | Power over Ethernet (PoE) ports quantity: 4 | Depth: 85 mm | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: Do not open the case or try to repair it yourself. | Uplink ports quantity: 1 | DC input voltage: 48 - 57 V | Packet forwarding rate (100 Mbps): 148800 pps | Fanless: Yes | Packet forwarding rate (10 Mbps): 14880 pps | Packet forwarding rate (1 Gbps): 1488000 pps | Rack mount kit: Yes

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950