

## **Mercusys MB110-4G wireless router Ethernet Single- band (2.4 GHz) White**



Model: MB110-4G

Manufacturer: MERCUSYS

EAN: 6957939001995

Product Code: 200117

## **R875**

Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Security algorithms: WPA2-PSK | Number of products included: 1 pc(s) | 4G standard: LTE-TDD & LTE-FDD | Ethernet LAN (RJ-45) ports: 2 | Ethernet LAN interface type: Ethernet | Universal Plug and Play (UPnP): Yes | Output voltage: 9 V | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Reset button: Yes | Security algorithms: WPA | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11g | Height: 150.5 mm | Operating relative humidity (H-H): 10 - 90% | Product type: Desktop/pole router | Dual SIM support: No | Storage temperature (T-T): -40 - 70 °C | Wi-Fi Multimedia (WMM)/(WME): Yes | WLAN data transfer rate (max): 300 Mbit/s | SIM card slot: Yes | Ethernet LAN: Yes | Width: 90 mm | Power source type: DC | Operating temperature (T-T): 0 - 40 °C | Security algorithms: 128-bit WEP | Ethernet LAN data rates: 100 | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | System event

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

log: Yes | DC-in jack: Yes | Cabling technology: 10/100Base-T(X) | DSL WAN: No | WAN connection type: RJ-45 | Ethernet WAN: Yes | Wi-Fi standards: 802.11b | Wi-Fi band: Single-band (2.4 GHz) | 3G standards: UMTS | 3G standards: HSPA+ | Depth: 92 mm | Weight: 710 g | Quick installation guide: Yes | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | 3G standards: HSPA | USB port: No | DHCP server: Yes | Package type: Box | Product colour: White | AC adapter included: Yes | Output current: 0.85 A | Warnings: Do not expose the device to water or moisture. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to extreme temperatures. | 3G/4G USB modem compatibility: Yes | 4G bands supported: 2100 | Mobile network generation: 4G | SIM card type: NanoSIM | WPS push button: Yes | 4G bands supported: 700 | 4G bands supported: 2300 | 4G bands supported: 800 | 3G bands supported: 2100 MHz | 3G bands supported: 850 | Indication light: Yes | VoIP protocols: IPv4, IPv6 | Port-based Network Access Control (PNAC): Yes | 3G bands supported: 900 | Firewall: Yes | Port triggering: Yes | Dynamic DNS (DDNS): Yes | Port forwarding: Yes | 4G bands supported: 900 | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 | DMZ support: Yes | 4G bands supported: 1800 | Antenna design: Internal

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950