

Tenda 4G05 wireless router Fast Ethernet Single-band (2.4 GHz) Black



Model: 4G05

Manufacturer: TENDA

EAN: 6932849430752

Product Code: 200144

R791

VPN support: VPN(PPTP Client/L2TP Client/PPTP Server) | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Antenna design: Internal & external | VPN server: PPTP Server | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not expose the device to water or moisture. | Sustainability compliance: Yes | Schedule access: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Supported network protocols: IPv4/IPv6 | Ethernet LAN interface type: Fast Ethernet | Wi-Fi standards: 802.11b | SIM card slot: Yes | DHCP server: Yes | Antennas quantity: 4 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Wi-Fi standards: 802.11g | DSL WAN: No | Depth: 127.4 mm | Ethernet LAN data rates: 100 | Weight: 134 g | Product type: Portable router | Firmware upgradeable: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Storage temperature (T-T): -30 - 70 °C | Ethernet LAN: Yes | Product colour: Black | Quick installation guide: Yes | LED indicators: LAN, LTE, WLAN | Quality of Service (QoS) support: Yes | AC input frequency: 50/60 Hz | Operating temperature (T-T): -5 - 45 °C | DHCP client: Yes | Ethernet LAN

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

data rates: 10 | Security algorithms: WPA2 | AC adapter included: Yes | Wi-Fi band: Single-band (2.4 GHz) | Output current: 1 A | Ethernet LAN (RJ-45) ports: 2 | Security algorithms: WPA2-PSK | Cables included: LAN (RJ-45) | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Output voltage: 5 - 9 V | USB port: No | WAN connection type: RJ-45 | WLAN data transfer rate (max): 300 Mbit/s | AC input voltage: 100 - 240 V | Ethernet WAN: Yes | 4G standard: LTE-TDD & LTE-FDD | DC-in jack: Yes | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.11b | Height: 26 mm | Security algorithms: WPA | 3G standards: WCDMA | Power source type: DC | Width: 90.5 mm | Reset button: Yes | WLAN data transfer rate (first band): 300 Mbit/s | WPS push button: Yes | 3G/4G USB modem compatibility: No | SIM card type: NanoSIM | Transmit power: 20 dBmW | Firewall: Yes | Guest access: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950