

TP-Link Archer AC1200 Wireless Dual Band 4G LTE Router



Model: Archer MR400

Manufacturer: TP-LINK

EAN: 6935364080662

Product Code: 200185

R1,807

VPN support: PPTP, L2TP, IPSec | Receiver sensitivity: 5GHz: 11a 54M: -74dBm 11ac HT20: -67dBm 11ac HT40: -64dBm 11ac HT80 : -60dBm 11n HT20: -71dBm 11n HT40: -70dBm 2.4G: 11g 54M: -76dBm 11n HT20: -73dBm 11n HT40: -67dBm | Certification: CE, RoHS | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows NT | Height: 33.5 mm | Windows operating systems supported: Windows 7 | VPN Passthrough: Yes | Product type: Tabletop router | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G bands supported: 2100 MHz | Windows operating systems supported: Windows XP Professional x64 | Output current: 1.5 A | Wall mountable: Yes | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows XP Home x64 | Cables included: LAN (RJ-45) | Wi-Fi standards: Wi-Fi 4 (802.11n) | WLAN data transfer rate (second band): 867 Mbit/s | Package height: 70 mm | Windows operating systems supported: Windows 2000 | On/off switch: Yes | SIM card type: MicroSIM | Universal Plug and Play (UPnP): Yes | 3G bands supported: 900 | Operating relative humidity (H-H): 10 - 90% | GSM bands supported: 1800 | GSM bands supported: 900 | Package width: 307 mm | 3G standards: UMTS | Detachable antenna(s): Yes | VPN tunnels quantity: 10 | 4G: Yes | Output voltage: 12 V | Access

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Control List (ACL): Yes | Guest access: Yes | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11b | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Cabling technology: 10/100Base-T(X) | 3G standards: HSPA | Windows operating systems supported: Windows 98SE | GSM bands supported: 850 | Wi-Fi standards: 802.11a | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | 3G standards: DC-HSPA+ | WLAN data transfer rate (first band): 450 Mbit/s | GSM bands supported: 1900 MHz | 3G standards: HSPA+ | 3G: Yes | Antennas quantity: 2 | Windows operating systems supported: Windows XP Professional | Mobile network generation: 4G | USB port: No | 2G standards: Edge | SIM card slot: Yes | Depth: 124.5 mm | 4G standard: LTE | 2G standards: GSM | 2G standards: GPRS | Windows operating systems supported: Windows 10 | 3G/4G USB modem compatibility: No | Ethernet LAN: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Firewall: Yes | Storage relative humidity (H-H): 5 - 90% | Ethernet WAN: Yes | Operating temperature (T-T): 0 - 40 °C | Supported network protocols: IPv4, IPv6 | Ethernet LAN interface type: Fast Ethernet | Firewall security: DoS, SPI Firewall, IP and MAC Address Binding | Transmit power: CE: 20dBm(2.4GHz), 23dBm(5GHz) | Antenna design: Internal & external | Port forwarding: Yes | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Mac compatibility: Yes | Quick installation guide: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 4G bands supported: 900 | AC adapter included: Yes | 4G bands supported: 1800 | VPN server: PPTP VPN, IPSec VPN, OpenVPN | Mac operating systems supported: MacOS | DSL WAN: No | WLAN data transfer rate (max): 867 Mbit/s | WPS push button: Yes | DoS attack prevention: Yes | Dynamic DNS (DDNS): Yes | Warnings: Do not expose the device to water or moisture. | Linux operating systems supported: Yes | WAN connection type: RJ-45 | Package depth: 223 mm | 4G bands supported: 2600 | 4G bands supported: 2100 | 4G bands supported: 800 | DHCP server: Yes | DMZ support: Yes | Warnings: Do not expose the device to extreme temperatures. | Memory card slot(s): No | Width: 174 mm | Harmonized System (HS) code: 85176990 | Ethernet LAN (RJ-45) ports: 3 | DHCP client: Yes | Package type: Box | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: WPA | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Stateful Packet Inspection (SPI): Yes | Security algorithms: WPA2-PSK | Ethernet LAN data rates: 10 | Networking standards: IEEE 802.11ac | LED indicators: LAN, Power, Status, WLAN | Security algorithms: WPA-PSK | Power source type: DC | Security algorithms: 128-bit WEP | Web-based management: Yes | Ethernet LAN data rates: 100 | Networking standards: IEEE 802.11b | Product colour: Black | Package weight: 670 g | DC-in jack: Yes | Reset button: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950