

TP-LINK TL- MR100 LTE wireless router Single-band (2.4 GHz) Black



Model: TL-MR100

Manufacturer: TP-LINK

EAN: 6935364088804

Product Code: 200186

R1,200

VPN support: PPTP, L2TP | Certification: CE, RoHS | Receiver sensitivity: 11g 54M: -74dBm11n HT20: -71dBm11n HT40: -68dBm | Height: 36 mm | Cables included: LAN (RJ-45) | Windows operating systems supported: Windows 8 | Wi-Fi standards: 802.11b | Product type: Tabletop router | Output voltage: 9 V | Universal Plug and Play (UPnP): Yes | Windows operating systems supported: Windows 7 | Dynamic DNS (DDNS): Yes | Storage temperature (T-T): -40 - 70 °C | 4G bands supported: 900 | 4G: Yes | SIM card slot: Yes | Windows operating systems supported: Windows 98SE | UMTS bands supported: 900 | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | On/off switch: Yes | Security algorithms: WPA2-PSK | WPS push button: Yes | Mac operating systems supported: Yes | Output current: 0.85 A | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Supported network protocols: IPv4, IPv6 | 3G: Yes | Antennas quantity: 2 | DC-in jack: Yes | Ethernet LAN data rates: 100 | Antenna connector type: N-type | MAC address filtering: Yes | 4G bands supported: 2100 | 4G bands supported: 800 | 4G bands

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

supported: 1900 | Power source type: DC | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 | Width: 154 mm | Ethernet LAN interface type: Ethernet | Linux operating systems supported: Yes | USB port: No | Security algorithms: WPA | Top Wi-Fi standard: 802.11b/g/n | 4G bands supported: 2300 | Ethernet LAN: Yes | Windows operating systems supported: Windows XP | UMTS bands supported: 2100 MHz | Operating relative humidity (H-H): 10 - 90% | Antenna type: External | Wi-Fi standards: 802.11g | WLAN data transfer rate (max): 300 Mbit/s | Guest access: Yes | 3G standards: UMTS | Product colour: Black | Quick installation guide: Yes | IP address filtering: Yes | Operating temperature (T-T): 0 - 40 °C | 4G bands supported: 2600 | 4G bands supported: 2500 | Windows operating systems supported: Windows NT | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi band: Single-band (2.4 GHz) | Ethernet LAN (RJ-45) ports: 2 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Windows operating systems supported: Windows 2000 | DHCP server: Yes | Package type: Box | DMZ support: Yes | Networking standards: IEEE 802.11b | 3G/4G USB modem compatibility: No | AC adapter included: Yes | 4G bands supported: 1800 | Ethernet LAN data rates: 10 | 3G standards: HSPA | Security algorithms: 128-bit WEP | Depth: 114 mm | Reset button: Yes | DHCP client: Yes | Ethernet WAN: Yes | 4G standard: LTE-TDD & LTE-FDD

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950