

TP-LINK 4G+ Cat6 AC1200 Wireless Dual Band Gigabit Router



Model: Archer MR600

Manufacturer: TP-LINK

EAN: 6935364089832

Product Code: 200187

R2,648

Receiver sensitivity: 5 GHz: 11a 54M: -74 dBm 11ac HT20: -66 dBm 11ac HT40: -63 dBm 11ac HT80 : -59 dBm 11n HT20: -73 dBm 11n HT40: -70 dBm 2.4 GHz: 11g 54M: -74 dBm 11n HT20: -72 dBm 11n HT40: -69 dBm | VPN support: PPTP VPN, IPSec VPN , OpenVPN | Certification: CE, RoHS | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11g | AC input frequency: 50 - 60 Hz | Filtering: Yes | Networking standards: IEEE 802.11ac | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 1000 Mbit/s | Networking standards: IEEE 802.11n | Product colour: Black | Stateful Packet Inspection (SPI): Yes | DHCP client: Yes | AC input voltage: 100 - 240 V | DC-in jack: Yes | Ethernet LAN data rates: 10 | Ethernet LAN (RJ-45) ports: 4 | Wi-Fi standards: 802.11b | Operating temperature (T-T): 0 - 40 °C | Wi-Fi standards: 802.11g | Wi-Fi standards: Wi-Fi 4 (802.11n) | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Mac operating systems supported: Yes | 3G: Yes | Antennas quantity: 2 | Security algorithms: WPA | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Security

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

algorithms: 128-bit WEP | 4G: Yes | Output voltage: 12 V | Security algorithms: WPA2-PSK | WLAN data transfer rate (max): 867 Mbit/s | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Power source type: AC, DC | Wi-Fi standards: 802.11a | Ethernet WAN: Yes | Windows operating systems supported: Yes | Cables included: LAN (RJ-45) | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package depth: 223 mm | Reset button: Yes | Quick installation guide: Yes | Package width: 307 mm | Package height: 70 mm | LED indicators: LAN, Power, WLAN | Ethernet LAN interface type: Gigabit Ethernet | Width: 229 mm | Operating relative humidity (H-H): 10 - 90% | AC adapter included: Yes | Package type: Box | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to water or moisture. | Guest access: Yes | 3G standards: HSPA | Antenna design: External | 3G standards: UMTS | Mobile network generation: 4G | Product type: Tabletop router | Number of guest networks (5 GHz): 1 | 3G/4G USB modem compatibility: No | WLAN data transfer rate (second band): 300 Mbit/s | Port forwarding: Yes | Port triggering: Yes | 4G bands supported: 2600 | 5G: No | Dual SIM support: No | WPS push button: Yes | DMZ support: Yes | Firewall security: Domain Filter, IP, MAC Address Binding | Height: 37 mm | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | 4G bands supported: 2100 | 4G bands supported: 800 | 3G bands supported: 850 | URL filtering: Yes | Universal Plug and Play (UPnP): Yes | SIM card type: MicroSIM | Firewall: Yes | WLAN data transfer rate (first band): 867 Mbit/s | Number of guest networks (2.4 GHz): 1 | 3G bands supported: 2100 MHz | USB port: No | 3G bands supported: 900 | Output current: 1.5 A | Dynamic DNS (DDNS): Yes | 4G bands supported: 700 | 4G bands supported: 2300 | Parental control: Yes | Wall mountable: No | DHCP server: Yes | Harmonized System (HS) code: 85176990 | 4G bands supported: 900 | Routing protocols: IP | 4G bands supported: 1800 | 4G bands supported: 850 | 4G bands supported: 2500 | 4G standard: LTE | Detachable antenna(s): Yes | Supported network protocols: IPv4, IPv6 | SIM card slot: Yes | Ethernet LAN: Yes | Depth: 160 mm | DSL WAN: No | DoS attack prevention: Yes | Number of products included: 1 pc(s) | WAN connection type: RJ-45 | Wi-Fi Multimedia (WMM)/(WME): Yes | Linux operating systems supported: Yes | Memory card slot(s): No

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950