

TP-Link Archer 5G AX1800 Wireless Dual- Band Gigabit Router



Model: ARCHER NX200

Manufacturer: TP-LINK

EAN: 8885020621075

Product Code: 200188

R5,591

VPN support: PPTP VPN, IPsec VPN, OpenVPN | 4G bands supported: 2100 | Detachable antenna(s): Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | 3G bands supported: 2100 MHz | 3G standards: UMTS | 3G bands supported: 850 | WLAN data transfer rate (second band): 1201 Mbit/s | Parental control: Yes | WLAN data transfer rate (first band): 574 Mbit/s | 3G bands supported: 900 | Mobile network generation: 5G | 3G standards: DC-HSDPA | 3G standards: HSPA | 4G standard: LTE-TDD & LTE-FDD | 5G bands supported: 850 | 4G bands supported: 700 | 4G bands supported: 2300 | MU-MIMO technology: Yes | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser | Number of guest networks (5 GHz): 1 | WAN connection type: RJ-45 | DoS attack prevention: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Linux operating systems supported: Yes | SIM card type: NanoSIM | WPS push button: Yes | Firewall: Yes | Port triggering: Yes | Dynamic DNS (DDNS): Yes | Firewall security: IPv4 SPI Firewall, IPv6 Firewall | DHCP server: Yes | SIM card slot: Yes | 4G bands supported: 1800 | 5G bands supported: 2100 | 4G

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

bands supported: 1500 | 5G bands supported: 3500 | 4G bands supported: 800 | 5G bands supported: 700 | 5G bands supported: 1800 | 5G bands supported: 2300 | 4G bands supported: 3700 MHz | 4G bands supported: 3500 | 5G bands supported: 2600 | 5G bands supported: 800 | 4G bands supported: 900 | 5G bands supported: 900 | Access Control List (ACL): Yes | Output current: 2 A | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 | 5G bands supported: 3700 MHz | DMZ support: Yes | Number of guest networks (2.4 GHz): 1 | USB port: No | Antenna design: Internal | 5G bands supported: 2500 | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Windows operating systems supported: Windows XP | Windows operating systems supported: Windows 2000 | Height: 190 mm | Windows operating systems supported: Windows 10 | Cables included: LAN (RJ-45) | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 7 | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows NT | Product type: Tabletop router | Ethernet WAN: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: 128-bit WEP | Networking standards: IEEE 802.11a | Quick installation guide: Yes | Networking standards: IEEE 802.11ax | Security algorithms: WPA | Product colour: White | AC adapter included: Yes | Networking standards: IEEE 802.11ac | Security algorithms: WPA2-PSK | WLAN data transfer rate (max): 1800 Mbit/s | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Output voltage: 12 V | Ethernet LAN data rates: 100 | Warnings: Do not expose the device to water or moisture. | Ethernet LAN interface type: Gigabit Ethernet | Networking standards: IEEE 802.11b | Ethernet LAN data rates: 10 | Warnings: Do not expose the device to extreme temperatures. | AC input frequency: 50/60 Hz | Width: 99 mm | On/off switch: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Ethernet LAN (RJ-45) ports: 3 | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11b | Operating relative humidity (H-H): 10 - 90% | Operating temperature (T-T): 0 - 40 °C | DHCP client: Yes | Ethernet LAN data rates: 1000 Mbit/s | Mac operating systems supported: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Power source type: AC | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Antennas quantity: 10 | Reset button: Yes | Supported network protocols: IPv4, IPv6 | Ethernet LAN: Yes | Depth: 99 mm | AC input voltage: 100 - 240 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950