

Router TP-Link ARCHER NX600 5G AX3600 Wireless Dual



Model: NX600

Manufacturer: TP-LINK

EAN: 8885020624878

Product Code: 200189

R6,883

VPN support: PPTP VPN, IPsec VPN, OpenVPN | Access Control List (ACL): Yes | Ethernet LAN interface type: Gigabit Ethernet | 4G bands supported: 3700 MHz | 4G bands supported: 3500 | USB port: No | Output current: 2 A | 5G bands supported: 3700 MHz | 4G bands supported: 2100 | 4G bands supported: 800 | WAN connection type: RJ-45 | AC input voltage: 100 - 240 V | 5G bands supported: 3500 | Product colour: White | AC adapter included: Yes | 4G bands supported: 1800 | 5G bands supported: 2100 | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 | Wi-Fi standards: 802.11b | Parental control: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 4G bands supported: 900 | Quick installation guide: Yes | 5G bands supported: 700 | 5G bands supported: 1800 | 5G bands supported: 2300 | Wi-Fi standards: 802.11g | Number of guest networks (5 GHz): 1 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Security algorithms: 128-bit WEP | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows XP | UMTS bands supported: 2100 MHz | Security algorithms: WPA2-PSK | WPS push button: Yes | 4G bands supported: 700 | 4G bands supported: 2300 | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Antennas quantity: 10 | WLAN data

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

transfer rate (second band): 2402 Mbit/s | 4G standard: LTE-TDD & LTE-FDD | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows NT | UMTS bands supported: 900 | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | UMTS bands supported: 850 | Antenna design: Internal | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Mobile network generation: 5G | Width: 99 mm | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser | Windows operating systems supported: Windows 7 | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Security algorithms: WPA | 5G bands supported: 2600 | 5G bands supported: 800 | 5G bands supported: 900 | Ethernet LAN data rates: 1000 Mbit/s | Mac operating systems supported: Yes | WLAN data transfer rate (first band): 1148 Mbit/s | Product type: Tabletop router | Operating relative humidity (H-H): 10 - 90% | WLAN data transfer rate (max): 3600 Mbit/s | 5G bands supported: 2500 | AC input frequency: 50/60 Hz | 3G standards: UMTS | Power source type: AC | Ethernet WAN: Yes | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | Windows operating systems supported: Windows 2000 | Height: 190 mm | DHCP client: Yes | DoS attack prevention: Yes | Cables included: LAN (RJ-45) | Windows operating systems supported: Windows 10 | 3G/4G USB modem compatibility: No | DHCP server: Yes | Wi-Fi standards: Wi-Fi 5 (802.11ac) | 3G standards: DC-HSDPA | Ethernet LAN data rates: 10 | 3G standards: HSPA | Ethernet LAN (RJ-45) ports: 2 | Firewall: Yes | Ethernet LAN data rates: 100 | Operating temperature (T-T): 0 - 40 °C | 5G bands supported: 850 | Output voltage: 12 V | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Depth: 99 mm | SIM card slot: Yes | Number of guest networks (2.4 GHz): 1 | Linux operating systems supported: Yes | SIM card type: NanoSIM | Ethernet LAN: Yes | On/off switch: Yes | Supported network protocols: IPv4, IPv6 | Firewall security: IPv4 SPI Firewall, IPv6 Firewall | DMZ support: Yes | Dynamic DNS (DDNS): Yes | Port triggering: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | WAN/Ethernet LAN ports quantity: 1 | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not expose the device to water or moisture. | Compliance certificates: RoHS | Compliance certificates: CE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950