

TP-Link TL- WR802N wireless router Fast Ethernet Single-band (2.4 GHz) Blue, White



Model: TL-WR802N

Manufacturer: TP-LINK

EAN: 6935364071714

Product Code: 200190

R464

Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 1 | DHCP client: Yes | Security algorithms: WPA-Enterprise | Security algorithms: WPA2 | Security algorithms: WPA2-Enterprise | Security algorithms: WPA | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | LED indicators: Activity, LAN, Power, WLAN | Product colour: Blue | Processor cores: 1 | Operating relative humidity (H-H): 10 - 90% | Filtering: Yes | Power source type: USB | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Ethernet LAN data rates: 100 | Networking standards: IEEE 802.11b | Stateful Packet Inspection (SPI): Yes | Reset button: Yes | Ethernet LAN data rates: 10 | DC-in jack: Yes | Product colour: White | AC adapter included: Yes | Package weight: 240 g |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Do not open the appliance housing - risk of electric shock. | Warnings: Avoid contact with liquids as this may cause electric shock. | Compliance certificates: Federal Communications Commission (FCC) | DoS attack prevention: Yes | Wi-Fi standards: 802.11b | Cabling technology: 10/100Base-T(X) | WLAN data transfer rate (max): 300 Mbit/s | Windows operating systems supported: Windows 8 Enterprise | Windows operating systems supported: Windows Vista Enterprise x64 | Windows operating systems supported: Windows 8.1 Enterprise x64 | Windows operating systems supported: Windows 8.1 Pro x64 | Windows operating systems supported: Windows 8.1 x64 | Mac operating systems supported: MacOS | Wi-Fi standards: 802.11g | Wi-Fi standards: Wi-Fi 4 (802.11n) | Windows operating systems supported: Windows Vista Home Basic x64 | Windows operating systems supported: Windows 7 Professional x64 | Height: 18 mm | Package width: 110 mm | Windows operating systems supported: Windows Vista Home Premium x64 | Windows operating systems supported: Windows XP Home x64 | Cables included: LAN (RJ-45) | USB port: Yes | Number of guest networks (2.4 GHz): 1 | Windows operating systems supported: Windows Vista Ultimate x64 | Windows operating systems supported: Windows 8 Enterprise x64 | Windows operating systems supported: Windows 8 Pro | Windows operating systems supported: Windows 7 Enterprise | 3G/4G USB modem compatibility: No | Built-in processor: Yes | Storage relative humidity (H-H): 5 - 90% | Antennas quantity: 2 | Port forwarding: Yes | Output voltage: 5 V | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | DMZ support: Yes | Firewall security: SPI | DSL WAN: No | On/off switch: Yes | Ethernet LAN interface type: Fast Ethernet | Transmit power: CE: , 20dBm(2.4GHz) , FCC: , 30dBm | Universal Plug and Play (UPnP): Yes | Port triggering: Yes | DHCP server: Yes | Depth: 57 mm | Package depth: 109 mm | Firewall: Yes | IP address filtering: Yes | Ethernet LAN: Yes | SIM card slot: No | Quick installation guide: Yes | Windows operating systems supported: Windows Vista Home Premium | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows 7 Starter x64 | Windows operating systems supported: Windows NT | Windows operating systems supported: Windows Vista Enterprise | Windows operating systems supported: Windows 8.1 Enterprise | Windows operating systems supported: Windows 7 Professional | VPN Passthrough: Yes | Dynamic DNS (DDNS): Yes | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Output current: 1 A | Supported network protocols: IPv4, IPv6 | Package height: 73.5 mm | Sustainability compliance: Yes | WAN connection type: RJ-45 | Wi-Fi band: Single-band (2.4 GHz) | Ethernet WAN: Yes | Windows operating systems supported: Windows XP Professional x64 | Product type: Portable router | Windows operating systems supported: Windows Vista Business | Windows operating systems supported:

Windows 8.1 | Windows operating systems supported: Windows Vista Ultimate | Windows operating

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

systems supported: Windows 7 Ultimate x64 | Antenna design: Internal | Linux operating systems supported: Yes | Windows operating systems supported: Windows 7 Home Basic x64 | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows Vista Home Basic | Windows operating systems supported: Windows 8 | Cables included: USB | Windows operating systems supported: Windows 8 x64 | Windows operating systems supported: Windows Vista Business x64 | Windows operating systems supported: Windows XP Professional | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 2000 | Windows operating systems supported: Windows 8 Pro x64 | Windows operating systems supported: Windows 8.1 Pro | Windows operating systems supported: Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Memory card slot(s): No | Harmonized System (HS) code: 85176990 | Width: 57 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950