

TP-Link AC1200 Wireless VDSL/ADSL Modem Router



Model: ARCHER VR300

Manufacturer: TP-LINK

EAN: 6935364081942

Product Code: 200200

R1,195

Certification: CE, RoHS, RCM | DHCP server: Yes | Package weight: 840 g | Windows operating systems supported: Yes | Output voltage: 12 V | On/off switch: Yes | 3G/4G USB modem compatibility: No | Height: 290 mm | 3G: No | Wi-Fi standards: 802.11g | Operating temperature (T-T): 0 - 40 °C | Wi-Fi standards: Wi-Fi 4 (802.11n) | WLAN data transfer rate (second band): 867 Mbit/s | Wi-Fi standards: 802.11b | Antennas quantity: 4 | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Firewall: Yes | Ethernet LAN interface type: Fast Ethernet | Package height: 76 mm | DSL WAN: Yes | Mac operating systems supported: Yes | Mac compatibility: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | 4G: No | WLAN data transfer rate (first band): 300 Mbit/s | Width: 385 mm | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Harmonized System (HS) code: 85176990 | Universal Plug and Play (UPnP): Yes | Ethernet WAN: Yes | Ethernet LAN (RJ-45) ports: 4 | Storage relative humidity (H-H): 5 - 90% | WLAN data transfer rate (max): 867 Mbit/s | WPS push button: Yes | Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11n): 20 dBmW | Ethernet LAN: Yes | SIM card slot: No | Operating relative humidity (H-H): 10 - 90% | Package depth: 240 mm | RJ-11 ports quantity: 1 | Depth: 76 mm |

Product type: Tabletop router | Cables included: Phone (RJ-11) | VDSL2: Yes | VPN Passthrough: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Cables included: LAN (RJ-45) | Dynamic DNS (DDNS): Yes | Package width: 330 mm | Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11b): 20 dBmW | ADSL: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | ADSL2+: Yes | Wi-Fi standards: 802.11a | Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11g): 20 dBmW | Linux operating systems supported: Yes | ADSL2: Yes | Output current: 1 A | AC adapter included: Yes | DMZ support: Yes | USB port: No | Antenna design: External | DHCP client: Yes | Warnings: Avoid contact with liquids as this may cause electric shock. | Quick start guide: Yes | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Security algorithms: WPA2 | Networking standards: IEEE 802.11a | Security algorithms: IPSec | Security algorithms: WPA | Warnings: Do not open the appliance housing - risk of electric shock. | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11h | Ethernet LAN data rates: 100 | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Product colour: Black | Ethernet LAN data rates: 10 | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11ac | Filtering: Yes | Networking standards: IEEE 802.11b | Security algorithms: WPA-PSK | Reset button: Yes | Network address translation (NAT): Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950