

TP-Link Archer AX5400 Dual- Band Gigabit Wi- Fi 6 Router, Black



Model: Archer AX73

Manufacturer: TP-LINK

EAN: 6935364010263

Product Code: 200201

R2,845

Packaging content: 1 x TP-Link Archer AX5400 Dual-Band Gigabit Wi-Fi 6 Router, Black | Ethernet LAN interface type: Gigabit Ethernet | USB port: Yes | On/off switch: Yes | Output voltage: 12 V | Universal Plug and Play (UPnP): Yes | Depth: 147.2 mm | Output current: 2.5 A | Product type: Portable router | Access Control List (ACL): Yes | IP address filtering: Yes | DSL WAN: No | Supported network protocols: IPv4, IPv6 | Ethernet LAN: Yes | SIM card slot: No | Harmonized System (HS) code: 85176990 | Width: 272.5 mm | Height: 49.2 mm | Antenna design: External | Antennas quantity: 6 | Cabling technology: 10/100/1000Base-T(X) | Support Samba (storage): Yes | Wi-Fi standards: 802.11a | Built-in processor: Yes | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Do not open the appliance housing - risk of electric shock. | Media server: Yes | Number of guest networks (5 GHz): 1 | Warnings: Avoid contact with liquids as this may cause electric shock. | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Number of guest networks (2.4 GHz): 1 | Compliance certificates: Federal Communications Commission (FCC) | Sustainability

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

compliance: Yes | Compliance certificates: RoHS | Compliance certificates: CE | MU-MIMO technology: Yes | Built-in FTP server: Yes | WPS push button: Yes | DoS attack prevention: Yes | Firewall: Yes | WAN connection type: RJ-45 | Port forwarding: Yes | 3G/4G USB modem compatibility: No | Dynamic DNS (DDNS): Yes | Port triggering: Yes | DMZ support: Yes | WLAN data transfer rate (first band): 4804 Mbit/s | WLAN data transfer rate (second band): 574 Mbit/s | Parental control: Yes | Web-based management: Yes | MAC address filtering: Yes | Product colour: Black | Filtering: Yes | DHCP client: Yes | Ethernet LAN data rates: 100 | Stateful Packet Inspection (SPI): Yes | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 1000 Mbit/s | Network address translation (NAT): Yes | Operating temperature (T-T): 0 - 40 °C | Package height: 38 mm | Cables included: LAN (RJ-45) | Package weight: 800 g | Processor cores: 3 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Ethernet LAN (RJ-45) ports: 4 | Networking standards: IEEE 802.11a | Processor frequency: 1500 MHz | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Security algorithms: WPA2 | Security algorithms: WPA2-Enterprise | Wi-Fi standards: 802.11g | Package width: 124 mm | Networking standards: IEEE 802.11g | Security algorithms: WPA-Enterprise | Networking standards: IEEE 802.11ax | Security algorithms: WPA | WLAN data transfer rate (max): 5400 Mbit/s | Networking standards: IEEE 802.11ac | Wi-Fi standards: Wi-Fi 4 (802.11n) | Package depth: 310 mm | Quick installation guide: Yes | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | Reset button: Yes | Modulation: 1024-QAM | Modulation: OFDM | Networking standards: IEEE 802.11b | AC adapter included: Yes | Wi-Fi standards: 802.11b | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power source type: DC | Ethernet WAN: Yes | Operating relative humidity (H-H): 10 - 90% | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Quantity per pack: 1 pc(s)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950