

TP-Link Omada Gigabit VPN Router



Model: TL-ER605

Manufacturer: TP-LINK

EAN: 6935364089597

Product Code: 200202

R1,405

Supported protocols: IPsec/PPTP/L2TP | Certification: CE, FCC, RoHS | NAT functionality: • One-to-One NAT • Multi-Net NAT • Virtual Server • Port Triggering • NAT-DMZ • FTP/H.323/SIP/IPSec/PPTP ALG, UPnP | VPN support: • 20 IPsec VPN Tunnels • LAN-to-LAN, Client-to-LAN • Main, Aggressive Negotiation Mode • DES, 3DES, AES128, AES192, AES256 Encryption Algorithm • IKEv1/v2 • MD5, SHA1 Authentication Algorithm • NAT Traversal (NAT-T) • Dead Peer Detection (DPD) • Perfect Forward Secrecy (PFS) • PPTP VPN Server • 10 PPTP VPN Clients • 16 Tunnels • PPTP with MPPE Encryption • L2TP VPN Server • 10 L2TP VPN Clients • 16 Tunnels • L2TP over IPSec • OpenVPN Server • 10 OpenVPN Clients • 16 OpenVPN Tunnels | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Security algorithms: SHA-1 | Ethernet LAN data rates: 1000 Mbit/s | Ethernet LAN (RJ-45) ports: 5 | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Windows operating systems supported: Windows 8 | Reset button: Yes | Windows operating systems supported: Windows XP | DHCP client: Yes | Windows operating systems supported: Windows 98SE | Package weight: 650 g | Windows operating systems supported: Windows NT | Storage relative humidity (H-H): 5 - 90% | Windows operating systems supported: Windows 2000 | Windows operating systems supported: Windows 7 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | Security algorithms: 128-bit AES | AC input frequency: 50 - 60 Hz | Ethernet LAN data rates: 100 | Windows operating systems supported: Windows 10 | Quick start guide: Yes | Power source type: AC | Product colour: Black | Storage temperature (T-T): -40 - 70 °C | Web-based management: Yes | Security algorithms: DES | Security algorithms: 192-bit AES | Security algorithms: 3DES | Security algorithms: MD5 | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Package width: 190 mm | AC input voltage: 120 - 240 V | LED indicators: LAN | LED indicators: USB | LED indicators: WAN | LED indicators: System | LED indicators: Activity | Ethernet LAN data rates: 10 | Network address translation (NAT): Yes | Networking standards: IEEE 802.3u | Security algorithms: 256-bit AES | Rack capacity: 1U | Internal memory type: DRAM | Manual: Yes | Firewall: Yes | USB ports quantity: 1 | Routing protocols: RIP-1 | Height: 25 mm | Routing protocols: RIP-2 | Cables included: AC | 3G/4G USB modem compatibility: No | DMZ support: Yes | Ethernet interface type: Gigabit Ethernet | Flash memory: 16 MB | Warnings: Avoid contact with liquids as this may cause electric shock. | Traffic control: Yes | SIM card slot: No | Warnings: The product may emit radio waves that may interfere with other electronic devices. | VLAN support: Yes | Depth: 101 mm | Supported network protocols: TCP/IP, DHCP, ICMP, NAT, PPPoE, SNMP, HTTP, DNS, IPsec, PPTP, L2TP | Flash memory: 128 MB | Warnings: Do not open the appliance housing - risk of electric shock. | DHCP server: Yes | ARP attack prevention: Yes | Package height: 60 mm | Embedded DRAM (eDRAM) memory: 128 MB | DSL WAN: No | Cabling technology: 10/100/1000Base-T(X) | Mac operating systems supported: MacOS | DoS attack prevention: Yes | System event log: Yes | Internal memory: 256 MB | Package depth: 254 mm | URL filtering: Yes | Quick installation guide: Yes | Universal Plug and Play (UPnP): Yes | Concurrent connections: 150000 | VPN tunnels quantity: 20 | Ethernet WAN: Yes | Authentication method: SHA-1, MD5 | Rack mounting: Yes | Power consumption (typical): 7.94 W | Policy-based routing: Yes | Management protocols: Telnet | Compliance certificates: RoHS | Linux operating systems supported: Yes | Width: 158 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950