

TP-Link Archer AX1800 Dual- Band Wi-Fi 6 Router



Model: Archer AX23

Manufacturer: TP-LINK

EAN: 4897098687048

Product Code: 200204

R1,173

NAT functionality: Port Forwarding, Port Triggering, UPnP, DMZ | Certification: FCC, CE, RoHS | Ethernet LAN data rates: 100 | Antenna connector type: SMA | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 1000 Mbit/s | Mac operating systems supported: Yes | DHCP client: Yes | Product colour: Black | Quick installation guide: Yes | WLAN data transfer rate (second band): 1201 Mbit/s | WAN connection type: RJ-45 | Wi-Fi standards: 802.11g | DC-in jack: Yes | Windows operating systems supported: Windows Vista Home Basic | Windows operating systems supported: Windows 10 Home x64 | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 8 Pro x64 | Windows operating systems supported: Windows 8.1 Pro | Windows operating systems supported: Windows 10 Pro | Windows operating systems supported: Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Windows operating systems supported: Windows 10 IoT Enterprise | Product type: Tabletop router | Operating temperature (T-T): 0 - 40 °C | Windows operating systems supported: Windows Vista Home Premium | Windows operating systems supported: Windows XP Home | Windows operating systems supported:

Windows 10 Home | Windows operating systems supported: Windows 7 Starter x64 | Height: 41.6

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

mm | Power source type: DC | Linux operating systems supported: Yes | Windows operating systems supported: Windows Vista Home Premium x64 | Windows operating systems supported: Windows 10 Education x64 | Windows operating systems supported: Windows XP Home x64 | Cables included: LAN (RJ-45) | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | Ethernet LAN (RJ-45) ports: 4 | Windows operating systems supported: Windows XP Professional x64 | Windows operating systems supported: Windows Vista Home Basic x64 | Windows operating systems supported: Windows 7 Professional x64 | USB port: No | Built-in processor: Yes | Windows operating systems supported: Windows Vista Business | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista Ultimate | Windows operating systems supported: Windows 7 Ultimate x64 | Windows operating systems supported: Windows Vista | Windows operating systems supported: Windows 7 x64 | Wi-Fi standards: 802.11b | Port forwarding: Yes | Guest access: Yes | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Windows operating systems supported: Windows Vista x64 | Package height: 395 mm | Windows operating systems supported: Windows 10 Pro x64 | Windows operating systems supported: Windows 8 Enterprise | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 2000 | Static route: Yes | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows Vista Ultimate x64 | Windows operating systems supported: Windows 10 IOT Core | Windows operating systems supported: Windows 8 Enterprise x64 | Windows operating systems supported: Windows 8 Pro | Windows operating systems supported: Windows 7 Enterprise | Antenna design: External | DHCP server: Yes | Package weight: 730 g | Windows operating systems supported: Windows Vista Enterprise | Windows operating systems supported: Windows 8.1 Enterprise | Windows operating systems supported: Windows 7 Professional | Windows operating systems supported: Windows 7 | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Depth: 135 mm | Windows operating systems supported: Windows 10 Enterprise x64 | Windows operating systems supported: Windows Vista Enterprise x64 | Windows operating systems supported: Windows 8.1 Enterprise x64 | Windows operating systems supported: Windows 8.1 Pro x64 | Windows operating systems supported: Windows 8.1 x64 | Windows operating systems supported: Windows 2000 Professional | Full duplex: Yes | Processor frequency: 1500 MHz | Security algorithms: WPA2-PSK | WPS push button: Yes | Universal Plug and Play (UPnP): Yes | Networking standards: IEEE 802.11b | Ethernet WAN: Yes | Windows operating systems supported: Windows 8 x64 | Windows operating systems supported: Windows Vista Business x64 | Windows operating systems supported: Windows 10

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Education | Windows operating systems supported: Windows XP Professional | Windows operating systems supported: Windows XP | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Windows operating systems supported: Windows 10 Enterprise | Windows operating systems supported: Windows 7 Home Basic x64 | Windows operating systems supported: Windows 98SE | Networking standards: IEEE 802.11ax | Security algorithms: WPA | DMZ support: Yes | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | System event log: Yes | Security algorithms: 128-bit WEP | Networking standards: IEEE 802.11a | Package width: 500 mm | Security algorithms: WMM | Ethernet LAN: Yes | SIM card slot: No | Web-based setup wizard: Yes | URL filtering: Yes | WLAN data transfer rate (first band): 574 Mbit/s | Access Control List (ACL): Yes | Networking standards: IEEE 802.11ac | Output current: 1 A | Bandwidth control: Yes | Web-based management: Yes | WLAN data transfer rate (max): 1800 Mbit/s | IP address filtering: Yes | Security algorithms: WPA-PSK | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | AC adapter included: Yes | 4G: Yes | Output voltage: 12 V | Wi-Fi standards: Wi-Fi 4 (802.11n) | Processor cores: 2 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Package depth: 350 mm | Warranty card: Yes | Flow control support: Yes | Harmonized System (HS) code: 85176990 | Network address translation (NAT): Yes | Width: 260.2 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950