

## TP-Link Archer AX72 wireless router Gigabit Ethernet Dual- band (2.4 GHz 5 GHz) Black



Model: ARCHER AX72

Manufacturer: TP-LINK

EAN: 4897098687215

Product Code: 200206

## R2,207

Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Wi-Fi standards: Wi-Fi 4 (802.11n) |  
Wi-Fi standards: 802.11b | Parental control: Yes | WLAN data transfer rate (second band): 574 Mbit/s  
| Wi-Fi standards: 802.11g | IP address filtering: Yes | Depth: 147.2 mm | Wi-Fi standards: Wi-Fi 5  
(802.11ac) | Ethernet LAN: Yes | DMZ support: Yes | Ethernet LAN interface type: Gigabit Ethernet |  
Dynamic DNS (DDNS): Yes | Port triggering: Yes | WPS push button: Yes | Universal Plug and Play  
(UPnP): Yes | Antennas quantity: 6 | Cabling technology: 10/100/1000Base-T(X) | Height: 49.2 mm |  
Firewall: Yes | WLAN data transfer rate (max): 5400 Mbit/s | Width: 272.5 mm | Port forwarding: Yes |  
Access Control List (ACL): Yes | Product type: Portable router | DSL WAN: Yes | USB port: Yes | On/off  
switch: Yes | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | WLAN data transfer rate (first band): 4804  
Mbit/s | DoS attack prevention: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Built-in processor: Yes  
| WAN connection type: RJ-45 | Product colour: Black | Networking standards: IEEE 802.11ax |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices  
may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or  
typographical errors. We recommend checking the current information before purchasing.

Security algorithms: WPA | Networking standards: IEEE 802.11g | Security algorithms: WPA-Enterprise | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Avoid contact with liquids as this may cause electric shock. | Networking standards: IEEE 802.11b | Filtering: Yes | Ethernet LAN data rates: 10 | Processor cores: 2 | Warnings: Do not open the appliance housing - risk of electric shock. | Power source type: DC | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.11a | Security algorithms: WPA2 | Security algorithms: WPA2-Enterprise | Web-based management: Yes | MAC address filtering: Yes | Ethernet LAN data rates: 1000 Mbit/s | Modulation: 1024-QAM | Ethernet LAN data rates: 100 | Modulation: OFDM | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | DHCP client: Yes | Network address translation (NAT): Yes | Ethernet LAN (RJ-45) ports: 4 | Networking standards: IEEE 802.11ac | Reset button: Yes | Ethernet WAN: Yes | Processor frequency: 1000 MHz | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | MU-MIMO technology: Yes | Support Samba (storage): Yes | Wireless Distribution System (WDS) bridge: Yes | Antenna design: External

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950