

TP-Link AX3000 Whole Home Mesh WiFi 6 System, 3-Pack



Model: DECO X50(3-PACK)

Manufacturer: TP-LINK

EAN: 4897098687086

Product Code: 200208

R4,075

AC adapter output current: 1.5 A | Ethernet LAN (RJ-45) ports: 3 | Operating temperature (T-T): 0 - 40 °C | DHCP client: Yes | Reset button: Yes | AC adapter output voltage: 12 V | Antenna type: Internal | Processor frequency: 1 GHz | Number of units included: 3 pc(s) | Package weight: 2.18 kg | Product colour: White | AC adapter included: Yes | Warnings: Avoid contact with liquids as this may cause electric shock. | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Do not open the appliance housing - risk of electric shock. | DC-in jack: Yes | Security algorithms: WPA-PSK | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK | Networking standards: IEEE 802.11ac | Compliance certificates: RoHS | Compliance certificates: CE | Package width: 369 mm | WLAN data transfer rate (first band): 574 Mbit/s | Depth: 110 mm | Wi-Fi standards: 802.11b | Parental control: Yes | Number of products included: 3 pc(s) | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Storage relative humidity (H-H): 5 - 90% | Height: 114 mm | Wi-Fi standards: 802.11g | Package height: 125 mm | Firewall security: SPI | Port forwarding: Yes | Wi-Fi standards: Wi-Fi 4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

(802.11n) | IGMP proxy: Yes | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Antennas quantity: 2 | WLAN data transfer rate (second band): 2402 Mbit/s | Dynamic DNS (DDNS): Yes | Transmit power: CE: 20 dBm (2.4 GHz) 23 dBm (5 GHz) FCC: 30 dBm (2.4 GHz) 30 dBm (5 GHz) | Built-in processor: Yes | IGMP snooping: Yes | Ethernet cable: Yes | Harmonized System (HS) code: 85171800 | Package depth: 276.5 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Width: 110 mm | Firmware upgradeable via: Network | Processor cores: 2 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Universal Plug and Play (UPnP): Yes | BeamForming: Yes | Parental control features: Custom profiles, Time controls, Weekly/monthly reports | Tagged VLAN: Yes | Number of guest networks (2.4 GHz): 1 | Number of guest networks (5 GHz): 1 | Operating relative humidity (H-H): 10 - 90% | MU-MIMO technology: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950