

TP-Link Omada AX3000 Gigabit VPN Router



Model: ER706W

Manufacturer: TP-LINK

EAN: 4895252500691

Product Code: 200216

R3,361

Certification: CE, FCC, RoHS | Ethernet LAN data rates: 1000 Mbit/s | DSL WAN: No | Wall mountable: Yes | Output voltage: 12 V | Ethernet LAN (RJ-45) ports: 4 | Product type: Desktop/pole router | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Security algorithms: WPA | Operating relative humidity (H-H): 10 - 90% | Output current: 2 A | Access Control List (ACL): Yes | Width: 226 mm | Filtering: Yes | Power source type: DC | Storage relative humidity (H-H): 5 - 90% | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Ethernet LAN data rates: 100 | Internal memory type: DDR4 | USB port: Yes | Antennas quantity: 3 | Cabling technology: 10/100/1000Base-T(X) | WLAN data transfer rate (max): 3000 Mbit/s | Antenna gain level (max): 4.5 dBi | Ethernet LAN interface type: Gigabit Ethernet | DHCP server: Yes | LED indicators: System, USB, WAN, WLAN | Height: 35 mm | Web-based management: Yes | Security algorithms: WPA2 | Ethernet LAN: Yes | Operating temperature (T-T): 0 - 40 °C | DC-in jack: Yes | Flash memory: 128 MB | Network address translation (NAT): Yes | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Product colour: Black | Internal memory: 512 MB | Manual: Yes | Security algorithms: WPA3-Enterprise | Depth: 131 mm | VPN tunnels quantity: 50 | Ethernet WAN: Yes | AC adapter included: Yes | Universal Plug and Play (UPnP): Yes | Ethernet LAN data rates: 10 | WLAN data transfer rate (first band): 574 Mbit/s | Routing protocols: OSPF | 3G/4G

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

USB modem compatibility: Yes | System event log: Yes | Antenna design: External | Routing protocols: RIP | WAN connection type: SFP | WLAN data transfer rate (second band): 2402 Mbit/s | URL filtering: Yes | SIM card slot: No | MU-MIMO technology: Yes | Dynamic DNS (DDNS): Yes | Guest access: Yes | Port triggering: Yes | Port forwarding: Yes | DMZ support: Yes | Schedule access: Yes | Warnings: Avoid contact with liquids as this may cause electric shock. | Warnings: Do not open the appliance housing - risk of electric shock. | Warnings: The product may emit radio waves that may interfere with other electronic devices.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950