

TP-Link 8-Port Gigabit Easy Smart Switch



Model: TL-SG108E

Manufacturer: TP-LINK

EAN: 6935364021856

Product Code: 200228

R699

Certification: FCC, CE, RoHS | Power source: DC | Input voltage: 9 V | Width: 158 mm | Operating relative humidity (H-H): 10 - 90% | Power supply included: Yes | Product colour: Black | Number of VLANs: 32 | User guide: Yes | 10G support: No | Power consumption (max): 3.55 W | Switching capacity: 16 Gbit/s | Forwarding rate: 11.9 Mpps | Basic switching RJ-45 Ethernet ports quantity: 8 | Cable types supported: Cat5 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package depth: 191 mm | IGMP snooping: Yes | Virtual LAN features: Port-based VLAN | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.1p | Package height: 92 mm | Cables included: AC | VLAN support: Yes | Housing material: Metal | Plug and Play: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Package width: 130 mm | Switch layer: L2 | Web-based management: Yes | Security algorithms: SNMP | Package weight: 630 g | Depth: 101 mm | Input current: 0.6 A | Loop protection: Yes | Heat dissipation: 12.12 BTU/h | Switch type: Managed | LED indicators: Yes | Auto MDI/MDI-X: Yes | Packet buffer memory: 1.5 MB | MAC address table: 4000 entries | Networking standards: IEEE 802.1ab | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 5 - 90% | Port mirroring: Yes | Store-and-forward: Yes | Auto-negotiation: Yes | Jumbo frames support: Yes | Security algorithms:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

SNMPv2 | Package type: Box | Broadcast storm control: Yes | Height: 25 mm | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | Cable types supported: Cat5e | Cable types supported: Cat3 | Cable types supported: Cat4 | Link aggregation: Yes | Jumbo frames: 15000 | Gigabit Ethernet (copper) ports quantity: 8

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950