

## TP-Link 8-Port Gigabit Easy Smart Switch with 4-Port PoE



Model: TL-SG108PE

Manufacturer: TP-LINK

EAN: 6935364094744

Product Code: 200229

## R1,200

Certification: FCC, CE, RoHS | Product colour: Black | Depth: 101 mm | LED indicators: Status | LED indicators: Activity | LED indicators: Power | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | User guide: Yes | Input current: 1.25 A | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Operating relative humidity (H-H): 10 - 90% | Web-based management: Yes | Operating temperature (T-T): 0 - 40 °C | Package weight: 890 g | Cables included: AC | Networking standards: IEEE 802.3i | Storage relative humidity (H-H): 5 - 95% | Input voltage: 48 V | Width: 158 mm | Package depth: 196 mm | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Power source: DC | Power over Ethernet (PoE): Yes | Power consumption (max): 65.2 W | Networking standards: IEEE 802.3u | Package type: Box | Package height: 121 mm | Package width: 131 mm | Auto MDI/MDI-X: Yes | Height: 25 mm | LED indicators: Link | LED indicators: PoE | LED indicators: Speed | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Ensure the unit is adequately ventilated during operation. |

**Warnings: Do not open the case or try to repair it yourself. | IGMP snooping: Yes | Basic switching RJ-**

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

45 Ethernet ports quantity: 8 | Power over Ethernet (PoE) power per port: 15.4 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Heat dissipation: 256.19 BTU/h | 10G support: No | VLAN support: Yes | Harmonized System (HS) code: 85176990 | Store-and-forward: Yes | Link aggregation: Yes | Gigabit Ethernet (copper) ports quantity: 8 | Virtual LAN features: Port-based VLAN | Broadcast storm control: Yes | Forwarding rate: 11.9 Mpps | Packet buffer memory: 1.5 MB | Power supply included: Yes | Jumbo frames: 15000 | Jumbo frames support: Yes | Power over Ethernet (PoE) ports quantity: 4 | Auto-negotiation: Yes | Cable types supported: Cat6 | MAC address table: 4000 entries | Cable types supported: Cat5 | Cable types supported: Cat5e | Number of VLANs: 32 | Cable types supported: Cat4 | Cable types supported: Cat3 | Port mirroring: Yes | Loop protection: Yes | Switch type: Managed | Switch layer: L2 | Switching capacity: 16 Gbit/s | Total Power over Ethernet (PoE) budget: 64 W

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950