

TP-Link 5-Port Gigabit Easy Smart Switch



Model: TL-SG105E

Manufacturer: TP-LINK

EAN: 6935364022037

Product Code: 200230

R505

Certification: FCC, CE, RoHS | Compatible operating systems: Microsoft Windows XP, Vista Windows 7, Windows 8, MAC OS, NetWare, UNIX / Linux | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Height: 26 mm | Power over Ethernet (PoE): No | Storage relative humidity (H-H): 5 - 90% | Input voltage: 5 V | Power source: DC | Cables included: AC | IGMP snooping: Yes | Operating relative humidity (H-H): 10 - 90% | Forwarding rate: 7.44 Mpps | Switching capacity: 10 Gbit/s | Quick start guide: Yes | Power consumption (max): 2.82 W | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 10BASE-T | VLAN support: Yes | Number of VLANs: 32 | Copper ethernet cabling technology: 1000BASE-T | Product colour: Black | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package height: 92 mm | Web-based management: Yes | User guide: Yes | Basic switching RJ-45 Ethernet ports quantity: 5 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Packet buffer memory: 1 MB | Auto-negotiation: Yes | Heat dissipation: 9.62 BTU/h | LED indicators: Yes | Input current: 0.6 A | Package depth: 125 mm | Width: 99.8 mm | Switch type: Unmanaged | 10G support: No | Depth: 98 mm | Virtual LAN features: Port-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

based VLAN | Power supply included: Yes | Switch layer: L2 | MAC address table: 2000 entries | Port mirroring: Yes | Package width: 128 mm | Rack mount kit: Yes | Package type: Box | Networking standards: IEEE 802.3u | Auto MDI/MDI-X: Yes | Link aggregation: Yes | Gigabit Ethernet (copper) ports quantity: 5 | Store-and-forward: Yes | Jumbo frames support: Yes | Jumbo frames: 16000

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950