

TP-Link 5-Port Gigabit Desktop PoE Switch with 4-Port



Model: TL-SG1005P

Manufacturer: TP-LINK

EAN: 6935364083212

Product Code: 200232

R953

Auto-negotiation: Yes | MAC address table: 2000 entries | Cable types supported: Cat3 | Harmonized System (HS) code: 85176990 | Power supply included: Yes | Cable types supported: Cat6 | Sustainability certificates: Federal Communications Commission (FCC) | 10G support: No | Forwarding rate: 7.44 Mpps | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Sustainability certificates: RoHS | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat4 | IGMP snooping: Yes | Sustainability certificates: CE | Switching capacity: 10 Gbit/s | Sustainability compliance: Yes | Flow control support: Yes | Rack mounting: No | MAC address auto-aging supported: Yes | DC input voltage: 48 V | Stackable: No | Basic switching RJ-45 Ethernet ports quantity: 5 | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-TX | Maximum cable length: 100 m | Copper ethernet cabling technology: 1000BASE-T | MAC address auto-learning supported: Yes | Fanless: Yes | Switch type: Unmanaged | Heat dissipation: 219.87 BTU/h | Gigabit Ethernet (copper) ports quantity: 5 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Store-and-forward: Yes | Package type: Box |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Package height: 121 mm | Package width: 131 mm | LED indicators: Yes | Operating relative humidity (H-H): 10 - 90% | Input current: 1.25 A | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3af | Operating temperature (T-T): 0 - 40 °C | Power over Ethernet (PoE) ports quantity: 4 | Networking standards: IEEE 802.3x | Total Power over Ethernet (PoE) budget: 56 W | Networking standards: IEEE 802.3u | Depth: 98 mm | Power consumption (max): 64.44 W | Product colour: Black | Power source: DC/PoE | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Auto MDI/MDI-X: Yes | Storage relative humidity (H-H): 5 - 90% | AC adapter included: Yes | User guide: Yes | Package depth: 196 mm | Height: 25 mm | Package weight: 800 g | Power over Ethernet (PoE): Yes | Width: 99.8 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950