

TP-Link 18-Port Gigabit Rackmount Switch with 16 PoE+



Model: TL-SG1218MP

Manufacturer: TP-LINK

EAN: 6935364072155

Product Code: 200240

R4,174

Certification: CE, FCC, RoHS | Total Power over Ethernet (PoE) budget: 250 W | Harmonized System (HS) code: 85176990 | Operating temperature (T-T): 0 - 50 °C | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Housing material: Metal | Auto MDI/MDI-X: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3u | Operating relative humidity (H-H): 10 - 90% | AC input frequency: 50 - 60 Hz | Product colour: Black | Package depth: 528 mm | 10G support: No | Depth: 180 mm | Flow control support: Yes | Full duplex: Yes | Package weight: 3.05 kg | Cables included: AC | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Form factor: 1U | Width: 440 mm | Power over Ethernet (PoE): Yes | Rack mounting: Yes | Heat dissipation: 977.44 BTU/h | Switch type: Unmanaged | Power source: AC | Combo SFP ports quantity: 2 | Height: 44 mm | LED indicators: Yes | Basic switching RJ-45 Ethernet ports quantity: 18 | Ethernet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

LAN data rates: 10,100,1000 Mbit/s | Storage relative humidity (H-H): 5 - 90% | Package width: 250 mm | Power supply included: Yes | Number of fans: 2 fan(s) | AC input voltage: 100 - 240 V | Package height: 80 mm | MAC address table: 8000 entries | Auto-negotiation: Yes | Packet buffer memory: 4.1 MB | Quick start guide: Yes | Power consumption (max): 286.64 W | Power over Ethernet plus (PoE+) ports quantity: 16 | Switching capacity: 36 Gbit/s | Jumbo frames support: Yes | Traffic classification: Yes | Gigabit Ethernet (copper) ports quantity: 18 | Jumbo frames: 10000 | Forwarding rate: 26.78 Mpps | MAC address auto-learning supported: Yes | Cable types supported: Cat4 | MAC address auto-aging supported: Yes | Cable types supported: Cat3 | Cable types supported: Cat6 | Cable types supported: Cat5 | Cable types supported: Cat5e | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: Do not open the case or try to repair it yourself. | Half duplex: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950