

TP-Link Omada 24-Port Gigabit L2+ Managed Switch with 4 10GE SFP+ Slots



Model: TL-SG3428X

Manufacturer: TP-LINK

EAN: 6935364010522

Product Code: 200243

R5,207

AC input frequency: 50/60 Hz | Web-based management: Yes | LED indicators: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3ae | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3i | Product colour: Black | AC input voltage: 100 - 240 V | Quick start guide: Yes | Heat dissipation: 80.52 BTU/h | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | Switch type: Managed | Form factor: 1U | Power source: AC | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Operating relative humidity (H-H): 10 - 90% | Depth: 180 mm | Packet buffer memory: 12 MB | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | 10G support: Yes | Power supply included: Yes | Storage relative humidity (H-H): 5 - 90% | Power consumption (max): 23.6 W | Power connector: AC-in jack | Flow control support: Yes | DHCP features: DHCP client | DHCP features: DHCP relay | DHCP features: DHCP server | Switching capacity: 128 Gbit/s | Switch layer: L2+/L3 | MIB support: Yes | VLAN support: Yes | Basic switching

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

RJ-45 Ethernet ports quantity: 24 | Cables included: LAN (RJ-45) | Port mirroring: Yes | Multicast support: Yes | DHCP features: DHCPv6 client | MAC address table: 16000 entries | Operating temperature (T-T): 0 - 45 °C | DHCP features: DHCP snooping | Number of fans: 0 fan(s) | Rack mounting: Yes | Height: 44 mm | IGMP snooping: Yes | Power over Ethernet (PoE): No | Width: 440 mm | Number of VLANs: 4000 | DHCP features: DHCPv6 snooping | Jumbo frames support: Yes | Management protocols: SNMPv1/v2c/v3, SNTP | IP-MAC-Port binding: Yes | Number of static routes: 48 | IPv4 & IPv6 features: IPv4/IPv6 access-control list (ACL) | IPv4 & IPv6 features: IPv6 ping | IPv4 & IPv6 features: IPv6 Telnet | Fanless: Yes | IPv4 & IPv6 features: IPv6 tracer | Rate limiting: Yes | Authentication: Guest VLAN, MAC-based authentication, Port-based authentication | SSH/SSL support: Yes | Head-of-line (HOL) blocking: Yes | Virtual LAN features: Protocol-based VLAN | Loop protection: Yes | Virtual LAN features: Tagged VLAN | Configuring Location Settings (CLI): Yes | Active link detection: Yes | Console port: RJ-45/micro-USB | Cloud-managed: Yes | BPDU filtering/protection: Yes | Authentication type: AAA, RADIUS, TACACS+ | GARP VLAN Registration Protocol (GVRP): Yes | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | Forwarding rate: 95.23 Mpps | Spanning tree protocol: Yes | Jumbo frames: 9000 | Store-and-forward: Yes | Link aggregation: Yes | System event log: Yes | Static route: Yes | Gigabit Ethernet (copper) ports quantity: 24 | Virtual LAN features: Voice VLAN | Virtual LAN features: Private VLAN | ARP inspection: Yes | IPv4 routes: 48 | Policy-based routing: Yes | IPv6 routes: 48 | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: Do not open the case or try to repair it yourself.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950