

TP-Link Omada 24-Port Gigabit L2+ Managed Switch with 4 SFP Slots



Model: TL-SG3428

Manufacturer: TP-LINK

EAN: 6935364010713

Product Code: 200245

R4,469

VLAN support: Yes | Rack mounting: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | IP-MAC-Port binding: Yes | Power over Ethernet (PoE): No | Basic switching RJ-45 Ethernet ports quantity: 24 | Height: 44 mm | Depth: 180 mm | Virtual LAN features: Tagged VLAN | Console port: RJ-45/micro-USB | Cloud-managed: Yes | Width: 440 mm | Head-of-line (HOL) blocking: Yes | Virtual LAN features: Voice VLAN | Multicast support: Yes | Cables included: LAN (RJ-45) | MAC address table: 16000 entries | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Web-based management: Yes | MAC address filtering: Yes | DHCP features: DHCP snooping | Switch layer: L2/L3 | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3ab | Storage relative humidity (H-H): 5 - 90% | System event log: Yes | DHCP features: DHCPv6 snooping | BPDU filtering/protection: Yes | Form factor: 1U | Operating temperature (T-T): 0 - 45 °C | DHCP features: DHCP server | DHCP features: DHCP client | DHCP features: DHCP relay | Management protocols: SNMPv1/v2c/v3, SNTTP | Forwarding rate: 41.66 Mpps | Power consumption (max): 20.6 W | Quick start guide: Yes | Switching

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

capacity: 56 Gbit/s | Packet buffer memory: 12 MB | GARP VLAN Registration Protocol (GVRP): Yes | Port mirroring: Yes | Power source: AC | Configuring Location Settings (CLI): Yes | Rate limiting: Yes | Number of VLANs: 4000 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Virtual LAN features: Protocol-based VLAN | Access Control List (ACL): Yes | Heat dissipation: 70.3 BTU/h | Loop protection: Yes | Virtual LAN features: Private VLAN | Flow control support: Yes | Networking standards: IEEE 802.3u | MIB support: Yes | Power supply included: No | Authentication type: AAA, RADIUS, TACACS+ | LED indicators: Yes | Static route: Yes | Operating relative humidity (H-H): 10 - 90% | IGMP snooping: Yes | AC input frequency: 50/60 Hz | AC input voltage: 100 - 240 V | IPv4 & IPv6 features: IPv6 Telnet | Switch type: Managed | Gigabit Ethernet (copper) ports quantity: 24 | IP routing: Yes | Product colour: Black | Networking standards: IEEE 802.3z | Number of static routes: 48 | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | IPv4 & IPv6 features: IPv6 tracer | 10G support: No | Jumbo frames support: Yes | Link aggregation: Yes | Policy-based routing: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | IPv4 routes: 48 | Store-and-forward: Yes | Authentication: MAC-based authentication, Port-based authentication | IPv4 & IPv6 features: IPv6 ping | ARP inspection: Yes | DHCP features: DHCPv6 client | Static port security: Yes | SSH/SSL support: Yes | IPv4 & IPv6 features: IPv4/IPv6 access-control list (ACL) | SFP module slots quantity: 4 | IPv6 routes: 48

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950