

TP-Link Omada 52-Port Gigabit L2+ Managed Switch with 48- Port PoE+



Model: TL-SG3452P

Manufacturer: TP-LINK

EAN: 6935364006273

Product Code: 200247

R13,428

Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: Do not open the case or try to repair it yourself. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Forwarding rate: 77.38 Mpps | Console port: RJ-45/micro-USB | Power over Ethernet plus (PoE+) ports quantity: 48 | Spanning tree protocol: Yes | Store-and-forward: Yes | Broadcast storm control: Yes | Link aggregation: Yes | MIB support: Yes | Access Control List (ACL): Yes | Loop protection: Yes | Switch type: Managed | Virtual LAN features: Protocol-based VLAN | Virtual LAN features: Voice VLAN | Virtual LAN features: Tagged VLAN | System event log: Yes | Virtual LAN features: MAC address-based VLAN | Rate limiting: Yes | Management protocols: SNMPv1/v2c/v3, SNTTP | Switch layer: L2/L3 | Authentication: MAC-based authentication, Port-based authentication | Flow control support: Yes | Virtual LAN features: Private VLAN | SSH/SSL support: Yes | Packet buffer memory: 12 MB | Power

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

connector: AC-in jack | Basic switching RJ-45 Ethernet ports quantity: 48 | Head-of-line (HOL) blocking: Yes | Cloud-managed: Yes | 10G support: No | Active link detection: Yes | GARP VLAN Registration Protocol (GVRP): Yes | Number of VLANs: 4000 | IP routing: Yes | Heat dissipation: 1584.08 BTU/h | MAC address table: 16000 entries | Port mirroring: Yes | Static route: Yes | Jumbo frames: 9000 | Number of static routes: 48 | SFP module slots quantity: 4 | IGMP snooping: Yes | Number of fans: 3 fan(s) | Quick start guide: Yes | Multicast support: Yes | Networking standards: IEEE 802.1D | DHCP features: DHCP client | Jumbo frames support: Yes | Policy-based routing: Yes | ARP inspection: Yes | DHCP features: DHCP relay | DHCP features: DHCPv6 snooping | BPDU filtering/protection: Yes | Form factor: 1U | Operating relative humidity (H-H): 10 - 90% | Storage relative humidity (H-H): 5 - 90% | Power supply included: Yes | Reset button: Yes | Power consumption (max): 464.2 W | Switching capacity: 104 Gbit/s | Cables included: AC | AC input voltage: 100 - 240 V | Manual: Yes | Product colour: Black | Password protection: Yes | Networking standards: IEEE 802.1w | Web-based management: Yes | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Package type: Box | DHCP features: DHCPv6 client | Ethernet LAN data rates: 10,100,1000 Mbit/s | LED indicators: Yes | DHCP features: DHCP server | AC input frequency: 50/60 Hz | Networking standards: IEEE 802.3x | DHCP features: DHCP snooping | Power over Ethernet (PoE) power per port: 30 W | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Height: 44 mm | Networking standards: IEEE 802.1p | Depth: 330 mm | VLAN support: Yes | Power over Ethernet (PoE): Yes | Total Power over Ethernet (PoE) budget: 384 W | Power source: AC | Rack mounting: Yes | Width: 440 mm | Operating temperature (T-T): 0 - 40 °C

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950