

## **TP-Link JetStream 48- Port Gigabit and 4-Port 10GE SFP+ L2+ Managed Switch with 48-Port PoE+**



Model: TL-SG3452XP

Manufacturer: TP-LINK

EAN: 6935364006495

Product Code: 200250

## **R15,677**

Certification: CE, FCC, RoHS | Networking standards: IEEE 802.3at | Width: 440 mm | Networking standards: IEEE 802.1Q | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.1D | ARP inspection: Yes | Forwarding rate: 130.9 Mpps | Quick start guide: Yes | IP-MAC-Port binding: Yes | Networking standards: IEEE 802.3ab | Rack mounting: Yes | Networking standards: IEEE 802.3af | Switching capacity: 176 Gbit/s | Harmonized System (HS) code: 85176990 | Power over Ethernet (PoE): Yes | IGMP snooping: Yes | Networking standards: IEEE 802.3u | Operating temperature (T-T): 0 - 40 °C | Total Power over Ethernet (PoE) budget: 500 W | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | AC input voltage: 100 - 240 V | Heat

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

dissipation: 2169.2 BTU/h | Switch type: Managed | Store-and-forward: Yes | Power source: AC | Static port security: Yes | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3ae | Authentication: Auto VLAN, Guest VLAN | Rate limiting: Yes | Product colour: Black | Networking standards: IEEE 802.1s | SSH/SSL support: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power over Ethernet (PoE) ports quantity: 48 | Operating relative humidity (H-H): 10 - 90% | AC input frequency: 50 - 60 Hz | 10G support: Yes | Internal memory: 512 MB | Port mirroring: Yes | Console port: RJ-45/micro-USB | Cloud-managed: Yes | Flow control support: Yes | Power supply included: Yes | MAC address table: 16000 entries | Networking standards: IEEE 802.1w | Form factor: 1U | Switch layer: L2+ | BPDU filtering/protection: Yes | System event log: Yes | Depth: 330 mm | DHCP features: DHCP client | DHCP features: DHCP relay | DHCP features: DHCP server | VLAN support: Yes | Basic switching RJ-45 Ethernet ports quantity: 48 | Height: 44 mm | Configuring Location Settings (CLI): Yes | Cables included: AC | Flash memory: 32 MB | Head-of-line (HOL) blocking: Yes | Multicast support: Yes | Storage relative humidity (H-H): 5 - 90% | Number of fans: 3 fan(s) | Jumbo frames: 9216 | Jumbo frames support: Yes | Networking standards: IEEE 802.3i | Spanning tree protocol: Yes | Link aggregation: Yes | Broadcast storm control: Yes | Rack rails: Yes

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950