

## TP-Link LiteWave 5-Port Gigabit Desktop Switch with 4- Port PoE+



Model: LS105GP

Manufacturer: TP-LINK

EAN: 4895252504545

Product Code: 200252

## R646

Certification: CE, FCC, RoHS | Product colour: Black | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3i | Package type: Box | AC input frequency: 50 Hz | Networking standards: IEEE 802.3u | 10G support: No | IGMP snooping: Yes | Power supply included: Yes | Operating relative humidity (H-H): 10 - 90% | LED indicators: Yes | AC input voltage: 220 V | User guide: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Switching capacity: 10 Gbit/s | Power over Ethernet (PoE): Yes | Basic switching RJ-45 Ethernet ports quantity: 5 | MAC address auto-aging supported: Yes | Forwarding rate: 7.44 Mpps | Power consumption (max): 74.46 W | Depth: 98 mm | Flow control support: Yes | Power source: DC/PoE | Cable types supported: Cat5 | Cable types supported: Cat5e | Width: 99.8 mm | Operating temperature (T-T): 0 - 40 °C | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Total Power over Ethernet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(PoE) budget: 65 W | DC input voltage: 53.5 V | Auto-negotiation: Yes | Power over Ethernet (PoE) ports quantity: 4 | Cable types supported: Cat3 | Cable types supported: Cat4 | Switch type: Unmanaged | MAC address auto-learning supported: Yes | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Ensure the unit is adequately ventilated during operation. | Storage relative humidity (H-H): 5 - 90% | Warnings: Do not open the case or try to repair it yourself. | Heat dissipation: 253.16 BTU/h | Height: 25 mm | Auto MDI/MDI-X: Yes | MAC address table: 2000 entries | Store-and-forward: Yes | Jumbo frames: 16000

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950