

TP-Link LiteWave LS105P Unmanaged Fast Ethernet (10/100) Power over Ethernet (PoE) Black



Model: LS105LP

Manufacturer: TP-LINK

EAN: 4895252504583

Product Code: 200253

R530

Certification: CE, FCC, RoHS | MAC address table: 2000 entries | Depth: 98 mm | Auto MDI/MDI-X: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Flow control support: Yes | User guide: Yes | 10G support: No | Product colour: Black | Package type: Box | Power over Ethernet (PoE): Yes | Auto-negotiation: Yes | Storage relative humidity (H-H): 5 - 90% | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3af | Power over Ethernet (PoE) power per port: 15.4 W | Power supply included: Yes | Cable types supported: Cat3 | DC input voltage: 53.5 V | Operating

temperature (T-T): 0 - 40 °C | Cable types supported: Cat4 | Basic switching RJ-45 Ethernet ports

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

quantity: 5 | Copper ethernet cabling technology: 100BASE-TX | AC input frequency: 50 Hz | Input current: 0.81 A | Operating relative humidity (H-H): 10 - 90% | Copper ethernet cabling technology: 10BASE-T | Width: 100 mm | Fanless: Yes | Jumbo frames support: Yes | Power consumption (max): 46.45 W | Power over Ethernet (PoE) ports quantity: 4 | Power source: DC/PoE | Cable types supported: Cat5 | Cable types supported: Cat5e | Wall mountable: Yes | Switch type: Unmanaged | Height: 25 mm | Networking standards: IEEE 802.3i | Forwarding rate: 0.744 Mpps | Switching capacity: 1 Gbit/s | LED indicators: Yes | AC input voltage: 220 V | Store-and-forward: Yes | Number of fans: 0 fan(s) | Heat dissipation: 157.93 BTU/h | Networking standards: IEEE 802.3u | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Do not open the case or try to repair it yourself.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950