

TP-Link LiteWave 10- Port Gigabit Desktop Switch with 8-Port PoE+



Model: LS1210GP

Manufacturer: TP-LINK

EAN: 4895252504569

Product Code: 200254

R1,235

Certification: CE, FCC, RoHS | Networking standards: IEEE 802.3i | AC input frequency: 50 Hz |
Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3ab | Networking standards:
IEEE 802.1p | Networking standards: IEEE 802.3at | Product colour: Black | Networking standards:
IEEE 802.3z | Networking standards: IEEE 802.3af | Package type: Box | LED indicators: Yes | AC input
voltage: 220 V | Networking standards: IEEE 802.3u | Depth: 126 mm | Operating temperature (T-T):
0 - 40 °C | Total Power over Ethernet (PoE) budget: 61 W | Switching capacity: 20 Gbit/s | Power
consumption (max): 76.96 W | Operating relative humidity (H-H): 10 - 90% | Power over Ethernet
(PoE) ports quantity: 8 | Power supply included: Yes | Basic switching RJ-45 Ethernet ports quantity: 9
| Power source: DC/PoE | Storage relative humidity (H-H): 5 - 90% | Power over Ethernet (PoE) power
per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Height:
26 mm | 10G support: No | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Yes | User guide: Yes | SFP module slots quantity: 1 | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Width: 209 mm | Auto MDI/MDI-X: Yes | Switch type: Unmanaged | Warnings: Ensure the unit is adequately ventilated during operation. | MAC address table: 4000 entries | Warnings: Do not open the case or try to repair it yourself. | Power over Ethernet (PoE): Yes | Heat dissipation: 261.66 BTU/h | DC input voltage: 53.5 V | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat4 | Flow control support: Yes | Cable types supported: Cat3 | Store-and-forward: Yes | Auto-negotiation: Yes | Jumbo frames: 16000 | Forwarding rate: 14.88 Mpps

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950