

## **TP-Link Omada ES220GMP network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black**



Model: ES220GMP

Manufacturer: TP-LINK

EAN: 8885020625943

Product Code: 200257

## **R4,469**

Unified static configuration: Yes | Zero Touch Provisioning (ZTP): Yes | Power source: AC | Operating temperature (T-T): -5 - 50 °C | Total Power over Ethernet (PoE) budget: 250 W | Flash memory: 64 MB | Package type: Box | Power over Ethernet (PoE): Yes | Width: 440 mm | User guide: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | VLAN support: Yes | Depth: 180 mm | Product colour: Black | Surge protection: Yes | Auto MDI/MDI-X: Yes | LED indicators: Yes | Rack mounting: Yes | Number of fans: 2 fan(s) | Jumbo frames support: Yes | AC input frequency:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

50/60 Hz | Operating relative humidity (H-H): 10 - 90% | Height: 44 mm | Firmware upgradeable: Yes | Power consumption (max): 289.7 W | Switching capacity: 40 Gbit/s | AC input voltage: 100 - 240 V | Noise level: 41.5 dB | Power supply included: Yes | Cables included: AC | Mean time between failures (MTBF): 310550.7 h | Networking standards: IEEE 802.3i | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3u | Web-based management: Yes | Networking standards: IEEE 802.1ab | Power over Ethernet (PoE) power per port: 30 W | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3z | SFP module slots quantity: 2 | Basic switching RJ-45 Ethernet ports quantity: 18 | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | 10G support: No | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 16 | Forwarding rate: 29.76 Mpps | Loop protection: Yes | Rack mount kit: Yes | Switch type: Managed | Surge protection voltage: 6 kV | Heat dissipation: 984.88 BTU/h | Switch layer: L2 | DHCP features: DHCP client | Virtual LAN features: MTU VLAN | Virtual LAN features: Port-based VLAN | Stackable: No | Virtual LAN features: Tagged VLAN | IGMP snooping: Yes | Number of VLANs: 32 | MAC address table: 8000 entries | Auto-negotiation: Yes | Cloud-managed: Yes | Store-and-forward: Yes | Gigabit Ethernet (copper) ports quantity: 18 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Link aggregation: Yes | Packet buffer memory: 4 MB | Port mirroring: Yes | Power over Ethernet (PoE) type supported: PoE+ | Jumbo frames: 15000 | Fast leave: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC)

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950