

TP-Link Omada ES206GP network switch Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Model: ES206GP

Manufacturer: TP-LINK

EAN: 1210002600644

Product Code: 200258

R1,264

Total Power over Ethernet (PoE) budget: 65 W | Switching capacity: 12 Gbit/s | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Power over Ethernet (PoE) type supported: PoE+ | Fanless: Yes | Product colour: Black | DC input voltage: 53.5 V | Basic switching RJ-45 Ethernet ports quantity: 6 | User guide: Yes | Surge protection voltage: 6 kV | Reset button: Yes | VLAN support: Yes | Networking standards: IEEE 802.1p | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.1ab | Power over Ethernet (PoE) power per port: 30 W | Basic

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Operating relative humidity (H-H): 10 - 90% | Width: 158 mm | MAC address table: 8000 entries | Auto-negotiation: Yes | IGMP snooping: Yes | Port mirroring: Yes | Power supply included: Yes | Wall mountable: Yes | Virtual LAN features: Port-based VLAN | Virtual LAN features: Tagged VLAN | Switch type: Managed | Loop protection: Yes | Power source: DC | Operating temperature (T-T): -5 - 40 °C | 10G support: No | Web-based management: Yes | Cloud-managed: Yes | Power over Ethernet plus (PoE+) ports quantity: 4 | Depth: 101 mm | Transmission distance (max): 0.25 km | Input current: 1.31 A | DHCP features: DHCP client | Forwarding rate: 7.4 Mpps | LED indicators: Yes | Power over Ethernet (PoE): Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Virtual LAN features: MTU VLAN | Store-and-forward: Yes | Jumbo frames: 15 | Surge protection: Yes | Gigabit Ethernet (copper) ports quantity: 6 | Link aggregation: Yes | Jumbo frames support: Yes | Package type: Box | Firmware upgradeable: Yes | AC adapter included: Yes | Height: 25 mm | Auto MDI/MDI-X: Yes | Packet buffer memory: 4 MB | Zero Touch Provisioning (ZTP): Yes | Fast leave: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Unified static configuration: Yes | Compliance certificates: Federal Communications Commission (FCC)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950