

ZTE MF986D SIM LTE kat.12



Model: MF986D

Manufacturer: ZTE POLAND

EAN: 6902176105081

Product Code: 200278

R1,405

VPN Passthrough: Yes | Set contents: Router, battery, 5V 2A charger, USB C cable, user manual, ErP declaration, warranty card | Mobile network generation: 5G | Functions: Firewall, port forwarding, IP/MAC/port/URL filter | Antenna design: Internal | Additional information: 1 x USB Type-C 3.0, 1 x SIM (Nano SIM 4FF), 2x TS-9 external antenna connectors Battery: 3000 mAh, replaceable, Platform: Qualcomm Snapdragon X12 + QCA6174A | Connectors: TS-9 external antenna connectors | Power adapter included: Yes | 4G standard: LTE Cat. 12/13 DL up to 600 Mbps, UL up to 150 Mbps FDD 1,2,3,4,5,26,7,8,20 12/17 28,32 TDD 38,40,41,42,43 Support 3CA for download, 2CA for upload UMTS 1/2/4/5/8 GSM 850/900/1800/1900 MHz UMTS 1/2/4 | Firewall: Yes | SIM card slot: Yes | Ethernet LAN: No | Universal Plug and Play (UPnP): Yes | SIM card type: NanoSIM | Auto MDI/MDI-X: Yes | Replaceable battery: Yes | Product type: Tabletop router | Security algorithms: WPA3-SAE | Depth: 14 mm | IP address filtering: Yes | LED indicators: Yes | Security algorithms: WMM | Product colour: White | Networking standards: IEEE 802.3u | Security algorithms: WPA2-PSK | WPS push button: Yes | Cables included: LAN (RJ-45) | Windows operating systems supported: Yes | Height: 107 mm | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | MAC address filtering: Yes | Wi-Fi standards: 802.11ac 2.4 | Weight: 150 g | Wi-Fi standards: 802.11g | Wi-Fi standards: IEEE 802.3u | Ethernet LAN data rates: 100 | Short Message Service (SMS): Yes | Width: 63 mm | Ethernet LAN

interface type: Gigabit Ethernet | Ethernet LAN data rates: 10 | Wi-Fi standards: 802.11a | WAN

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

connection type: RJ-45 | Ethernet LAN data rates: 1000 Mbit/s | Mac operating systems supported: Yes | Ethernet WAN: Yes | Wi-Fi standards: IEEE 802.3 | Wi-Fi standards: 802.11n | Wi-Fi standards: 802.11ac | Networking standards: IEEE 802.3 | Browser supported: Microsoft Internet Explorer 9.0+, Microsoft Edge 14.0, Firefox 60.0, Chrome 60.0, Safari 10.0, Opera 51.2 | Interface: LCD 1,44” 128x128 pix | SSID-based VLAN assignment: Yes | Security algorithms: WPA-PSK | DHCP server: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to water or moisture.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950