

Mikrotik cAP ac 867 Mbit/s White Power over Ethernet (PoE)



Model: RBcAPGi-5acD2nD

Manufacturer: MIKROTIK

EAN: 4752224003416

Product Code: 200741

R1,623

Receiver sensitivity: 2.4GHz: 1MBit/s: -100 @ 26dBm Tx 11MBit/s: -94 @ 26dBm Tx 6MBit/s: -96 @ 26dBm Tx 54MBit/s: -78 @ 23dBm Tx MCS0: -96 @ 26dBm Tx MCS7: -73 @ 22dBm Tx 5GHz: 6MBit/s: -96 @ 26dBm Tx 54MBit/s: -80 @ 21dBm Tx MCS0: -96 @ 26dBm Tx MCS7: -75 @ 20dBm Tx MCS9: -70 @ 18dBm Tx | Certification: CE, FCC, IC, EAC, ROHS | Maximum data transfer rate: 867 Mbit/s | Ethernet LAN data rates: 1000 Mbit/s | 5 GHz: Yes | 2.4 GHz: Yes | Product colour: White | Ethernet LAN data rates: 100 | Frequency band: 2.412 - 2.484, 5.15 - 5.875 GHz | Ethernet LAN data rates: 10 | Antenna type: Internal | Warnings: Do not use in damp conditions. | Warnings: Make sure the unit is stably mounted and ventilated. | Warnings: Do not open the appliance - risk of electric shock. | Ethernet LAN (RJ-45) ports: 2 | Processor frequency: 716 MHz | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | LED indicators: Yes | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.11ac | Depth: 30 mm | Power over Ethernet (PoE)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

type supported: Passive PoE | Maximum data transfer rate (5 GHz): 867 Mbit/s | Harmonized System (HS) code: 85176990 | Power over Ethernet (PoE) type supported: Active PoE | Height: 136 mm | AC adapter included: Yes | Antennas quantity: 4 | Power consumption (max): 13 W | Built-in processor: Yes | Placement: Ceiling, Wall | PoE adapter included: Yes | Processor model: IPQ4018 | Output voltage: 57 V | Antenna gain level (max): 2.5 dBi | Mounting kit: Yes | Power over Ethernet (PoE): Yes | Internal memory: 128 MB | Flash memory: 16 MB | Width: 136 mm | Operating system installed: RouterOS | Antenna features: Integrated antenna | Internal: No | Maximum data transfer rate (2.4 GHz): 300 Mbit/s | DC voltage range: 17 - 57 V | Operating temperature (T-T): -40 - 50 °C

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950