

TP-Link 16-Port Gigabit Desktop/Rackmount Network Switch



Model: TL-SG1016D

Manufacturer: TP-LINK

EAN: 6935364020613

Product Code: 200786

R1,405

Compatible operating systems: Microsoft Windows 2000/XP/2003/Vista/2008/7/2012/8/10 MacOS
NetWare UNIX Linux | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) |
Networking standards: IEEE 802.3x | Width: 294 mm | Sustainability compliance: Yes | MAC address
table: 8000 entries | Auto-negotiation: Yes | Harmonized System (HS) code: 85176990 |
Sustainability certificates: CE | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet
cabling technology: 1000BASE-T | Package height: 80 mm | Power over Ethernet (PoE): No | Basic
switching RJ-45 Ethernet ports quantity: 16 | Copper ethernet cabling technology: 10BASE-T |
Sustainability certificates: RoHS | Forwarding rate: 23.8 Mpps | Full duplex: Yes | Rack mounting: Yes
| Height: 44 mm | Storage relative humidity (H-H): 5 - 90% | Sustainability certificates: Federal
Communications Commission (FCC) | Package width: 250 mm | Cables included: AC | Package
weight: 1.85 kg | Cable types supported: Cat3 | LED indicators: Yes | Switching capacity: 32 Gbit/s |
Power connector: AC-in jack | Copper ethernet cabling technology: 1000BASE-TX | User guide: Yes |
Power consumption (max): 9.26 W | Rack mount kit: Yes | 10G support: No | Product colour: Black |
Storage temperature (T-T): -40 - 70 °C | Package depth: 400 mm | Flow control support: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Networking standards: IEEE 802.3ab | Cable types supported: Cat5 | Cable types supported: Cat5e | Power source: AC | Cable types supported: Cat4 | Heat dissipation: 31.6 BTU/h | AC input voltage: 100 - 240 V | Switch type: Unmanaged | Auto MDI/MDI-X: Yes | Depth: 180 mm | Stackable: Yes | Supported network protocols: CSMA/CD, TCP/IP | Package type: Box | Networking standards: IEEE 802.3u | Operating relative humidity (H-H): 10 - 90% | Power supply included: Yes | AC input frequency: 50/60 Hz | Operating temperature (T-T): 0 - 40 °C | Fanless: Yes | Jumbo frames: 10000 | Jumbo frames support: Yes | Gigabit Ethernet (copper) ports quantity: 16 | Maximum cable length: 100 m | Store-and-forward: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950