

TP-Link TL-SF1005D Managed Fast Ethernet (10/100) White



Model: TL-SF1005D

Manufacturer: TP-LINK

EAN: 6935364020064

Product Code: 200787

R276

Certification: FCC, RoHS | AC input frequency: 50 Hz | Package weight: 190 g | Input current: 0.6 A | LED indicators: Yes | AC input voltage: 220 V | Networking standards: IEEE 802.3x | Web-based management: Yes | Product colour: White | Ethernet LAN data rates: 10,100 Mbit/s | Warnings: Do not open the case or try to repair it yourself. | Package type: Box | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Networking standards: IEEE 802.3u | Supported network protocols: CSMA/CD, TCP/IP | Power supply included: No | Operating relative humidity (H-H): 10 - 90% | Height: 22 mm | Power consumption (max): 1.87 W | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package depth: 108 mm | Switching capacity: 1.6 Gbit/s | Power connector: DC-in jack | 10G support: No | Spanning tree protocol: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Power over Ethernet (PoE): No | User guide: Yes | MAC address table: 1000 entries | Operating temperature (T-T): 0 - 40 °C | Flow control support: Yes | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Depth: 70 mm | AC adapter included: Yes | Fast Ethernet (copper) ports quantity: 5 | DC input voltage: 5 V | Cables included: AC | Width: 103.5 mm | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | Power source: DC | Basic switching RJ-45 Ethernet ports quantity: 5 | Package width: 91 mm | Rack mounting: No | Auto MDI/MDI-X: Yes | Full duplex: Yes | Storage relative humidity (H-H): 5 - 90% | Package height: 85 mm | Store-and-forward: Yes | Auto-negotiation: Yes | Heat dissipation: 6.38 BTU/h | Power consumption (typical): 1.87 W | Switch type: Managed | Sustainability compliance: Yes | Fanless: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950