

TP-Link 24-Port Gigabit Desktop/Rackmount Network Switch



Model: TL-SG1024D

Manufacturer: TP-LINK

EAN: 6935364020620

Product Code: 200788

R1,967

Certification: FCC, CE, RoHS | Connectivity LEDs: Y | Operating temperature (T-T): 32 - 104 °F | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat3 | Supported network protocols: CSMA/CD, TCP/IP | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Forwarding rate: 35.7 Mpps | Power connector: DC-in jack | Cable types supported: Cat4 | MAC address table: 8000 entries | Auto-negotiation: Yes | Harmonized System (HS) code: 85176990 | Basic switching RJ-45 Ethernet ports quantity: 24 | Full duplex: Yes | Rack mounting: Yes | Flow control support: Yes | Height: 44 mm | Switching capacity: 48 Gbit/s | Rack mount kit: Yes | 10G support: No | Auto MDI/MDI-X: Yes | Stackable: Yes | Power requirements: 100 - 240V, 50/60Hz | Bandwidth: 48 Gbit/s | Maximum data transfer rate: 1 Gbit/s | Store-and-forward: Yes | Switch type: Unmanaged | Jumbo frames support: Yes | Heat dissipation: 46.44 BTU/h | Supported data transfer rates: 10/100/100 Mbps | Power supply included: Yes | Gigabit Ethernet (copper) ports quantity: 24 | Jumbo frames: 10000 | Product colour: Grey | Power consumption (max): 13.62 W | Operating temperature (T-T): 0 - 40 °C | LED indicators: Yes | Package type: Box | Connectivity technology:

Wired | Dimensions (WxDxH): 294 x 180 x 44 mm | Power over Ethernet (PoE): No | Networking

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

standards: IEEE 802.3x | Cables included: AC | Width: 294 mm | User guide: Yes | Networking standards: IEEE 802.3ab | Operating relative humidity (H-H): 10 - 90% | Package weight: 1.95 kg | Depth: 180 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package width: 250 mm | AC input frequency: 50 - 60 Hz | Package depth: 400 mm | Power source: AC | Networking standards: IEEE 802.3u | Networking features: Gigabit Ethernet | Package height: 80 mm | AC input voltage: 100 - 240 V | Storage relative humidity (H-H): 5 - 90%

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950