

## TP-Link 8-Port Gigabit Desktop PoE Switch with 4-Port



Model: TL-SG1008P

Manufacturer: TP-LINK

EAN: 6935364021160

Product Code: 200790

## R1,100

Cable types supported: Cat4 | Quality of Service (QoS) support: No | Fanless: Yes | Power supply included: Yes | Operating relative humidity (H-H): 10 - 90% | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 10BASE-T | Basic switching RJ-45 Ethernet ports quantity: 8 | Power source: DC/PoE | Cable types supported: Cat5 | Cable types supported: Cat5e | Power over Ethernet (PoE) ports quantity: 4 | Cable types supported: Cat3 | Copper ethernet cabling technology: 1000BASE-T | MAC address auto-learning supported: Yes | Package height: 68 mm | 10G support: No | Flow control support: Yes | Storage temperature (T-T): -40 - 70 °C | User guide: Yes | Package depth: 280 mm | Heat dissipation: 225.75 BTU/h | Switch type: Managed | Number of power supply units: 1 | MAC address auto-aging supported: Yes | Height: 27 mm | MAC address table: 4000 entries | Power connector: DC-in jack | Package width: 223 mm | Forwarding rate: 11.904 Mpps | DC input voltage: 53.5 V | Storage relative humidity (H-H): 5 - 90% | Cables included: AC | Total Power over Ethernet (PoE) budget: 64 W | Power over Ethernet (PoE): Yes | Switching capacity: 16 Gbit/s | Width: 171 mm | IGMP snooping: Yes | Depth: 98 mm | Stackable: No | Auto-negotiation: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Housing material: Metal |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Sustainability certificates: CE | Rack mounting: No | Sustainability compliance: Yes | Sustainability certificates: Federal Communications Commission (FCC) | Sustainability certificates: RoHS | Power consumption (max): 75 W | Auto MDI/MDI-X: Yes | Jumbo frames support: Yes | Jumbo frames: 16000 | Maximum cable length: 100 m | Store-and-forward: Yes | Gigabit Ethernet (copper) ports quantity: 8 | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | LED indicators: Yes | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3i | Package weight: 900 g | Networking standards: IEEE 802.3af | AC input voltage: 100 - 240 V | Product colour: Grey | Package type: Box | Input current: 1.31 A | AC input frequency: 50/60 Hz | Networking standards: IEEE 802.3u

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950