

TP-Link 24-Port Gigabit Easy Smart Switch



Model: TL-SG1024DE

Manufacturer: TP-LINK

EAN: 6935364021245

Product Code: 200792

R2,320

Certification: FCC, CE, RoHS | Compatible operating systems: Windows 98SE, NT, 2000, XP, Vista, Windows 7, Windows 8, MAC OS, NetWare, UNIX, Linux | Rate limiting: Yes | Form factor: 1U | Power consumption (max): 14.86 W | Cable types supported: Cat3 | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 10BASE-T | Operating relative humidity (H-H): 10 - 90% | Package height: 80 mm | Rack mounting: Yes | VLAN support: Yes | AC input frequency: 50 - 60 Hz | Basic switching RJ-45 Ethernet ports quantity: 24 | Switch layer: L2 | Heat dissipation: 114.37 BTU/h | AC input voltage: 100 - 240 V | Loop protection: Yes | LED indicators: Yes | Number of queues: 4 | Depth: 180 mm | Virtual LAN features: Tagged VLAN | Virtual LAN features: Port-based VLAN | Operating temperature (T-T): 0 - 40 °C | Package width: 250 mm | Forwarding rate: 35.7 Mpps | Switching capacity: 48 Gbit/s | Switch type: Managed | Copper ethernet cabling technology: 1000BASE-T | Package weight: 2.02 kg | Cables included: AC | Package type: Box | Cable types supported: Cat6 | MAC address table: 8000 entries | Auto-negotiation: Yes | Cable types supported: Cat5 | Package depth: 400 mm | Flow control support: Yes | Product colour: Black | User guide: Yes | Height: 44 mm | Networking standards: IEEE 802.1Q | Power supply included: Yes | Number of VLANs: 32 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 10G

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

support: No | IGMP snooping: Yes | Power source: AC | Packet buffer memory: 0.512 MB | Rack mount kit: Yes | Web-based management: Yes | Harmonized System (HS) code: 85176990 | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Port mirroring: Yes | Auto MDI/MDI-X: Yes | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3x | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Width: 294 mm | Networking standards: IEEE 802.3u | Gigabit Ethernet (copper) ports quantity: 24 | Jumbo frames: 9216 | Jumbo frames support: Yes | Link aggregation: Yes | Broadcast storm control: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950