

TP-Link 8-Port Gigabit Desktop Network Switch



Model: TL-SG1008D

Manufacturer: TP-LINK

EAN: 6935364092313

Product Code: 200794

R562

Storage temperature (T-T): -40 - 70 °C | Product colour: Black | Warnings: Ensure the unit is adequately ventilated during operation. | Power over Ethernet (PoE): No | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Ethernet LAN data rates: 10,100,480,800,1000 Mbit/s | Package weight: 300 g | AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.3x | LED indicators: Yes | AC input voltage: 100 - 240 V | Input current: 0.6 A | Operating temperature (T-T): 0 - 40 °C | Compliance certificates: Federal Communications Commission (FCC) | Warnings: Do not open the case or try to repair it yourself. | Compliance certificates: RoHS | Compliance certificates: CE | Power consumption (max): 3.53 W | Package width: 110 mm | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3i | Package type: Box | AC adapter included: Yes | Networking standards: IEEE 802.3u | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Height: 25.5 mm | Cable types supported: Cat3 | Cable types supported: Cat5 | Cable types supported: Cat5e | Package depth: 185 mm | User guide: Yes | Stackable: No | MAC address table: 4000 entries | Cable

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

types supported: Cat4 | Depth: 90 mm | Auto MDI/MDI-X: Yes | Power connector: DC-in jack | DC input voltage: 9 V | Copper ethernet cabling technology: 1000BASE-T | Basic switching RJ-45 Ethernet ports quantity: 8 | Packet buffer memory: 2 MB | Auto-negotiation: Yes | 10G support: No | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-TX | Cables included: AC | Switching capacity: 16 Gbit/s | Package height: 85 mm | Flow control support: Yes | Heat dissipation: 15.8 BTU/h | Switch type: Unmanaged | Wall mountable: Yes | Harmonized System (HS) code: 85176990 | Power source: DC | Sustainability compliance: Yes | Gigabit Ethernet (copper) ports quantity: 8 | Store-and-forward: Yes | Maximum cable length: 100 m | Rack mounting: No | Width: 180 mm | Jumbo frames support: Yes | Jumbo frames: 15000 | Power supply included: Yes | Fanless: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950