

TP-Link 5-Port Gigabit Desktop Network Switch



Model: TL-SG1005D

Manufacturer: TP-LINK

EAN: 6935364091798

Product Code: 200795

R350

Compatible operating systems: Microsoft Windows 2000/XP/2003/Vista/2008/7/2012/8/10, MacOS, NetWare, UNIX, Linux | Package weight: 180 g | Power connector: DC-in jack | Operating relative humidity (H-H): 10 - 90% | Power over Ethernet (PoE): No | Power consumption (max): 2.47 W | Switching capacity: 10 Gbit/s | Height: 28 mm | Harmonized System (HS) code: 85176990 | AC input voltage: 100 - 240 V | Input current: 0.6 A | Power source: DC | AC input frequency: 50/60 Hz | Package depth: 145 mm | Heat dissipation: 8.22 BTU/h | Operating temperature (T-T): 0 - 40 °C | Package width: 108 mm | Product colour: Black | Networking standards: IEEE 802.3x | Flow control support: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Switch type: Unmanaged | Power supply included: No | LED indicators: Yes | 10G support: No | Basic switching RJ-45 Ethernet ports quantity: 5 | Input voltage: 9 V | Width: 165 mm | Depth: 108 mm | MAC address table: 8000 entries | Auto-negotiation: Yes | Quick start guide: Yes | Full duplex: Yes | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Storage relative humidity (H-H): 5 - 90% | Warnings: Do not open the case or try to repair it yourself. | Package height: 85 mm | Warnings: Ensure the unit is adequately ventilated during operation. | Rack mounting: No |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Auto MDI/MDI-X: Yes | Storage temperature (T-T): -40 - 70 °C | Networking standards: IEEE 802.3u | Number of fans: 0 fan(s) | Jumbo frames support: Yes | Fanless: Yes | Gigabit Ethernet (copper) ports quantity: 5 | MAC address auto-aging supported: Yes | Half duplex: Yes | Jumbo frames: 15000 | Stackable: No | Store-and-forward: Yes | Maximum cable length: 100 m | MAC address auto-learning supported: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950