

## Zyxel NWA50AX 1775 Mbit/s White Power over Ethernet (PoE)



Model: NWA50AX-EU0102F

Manufacturer: ZYXEL

EAN: 4718937618743

Product Code: 200825

## R1,908

Operating relative humidity (H-H): 10 - 90% | Master (outer) case length: 483 mm | Master (outer) case gross weight: 13 kg | Width: 140 mm | Maximum data transfer rate (2.4 GHz): 575 Mbit/s | Placement: Ceiling, Wall | Auto Wireless Distribution System (WDS): Yes | Output voltage: 12 V | Products per master (outer) case: 20 pc(s) | Fast roaming: Yes | Harmonized System (HS) code: 85176990 | VLAN support: Yes | Master (outer) case height: 332 mm | Depth: 140 mm | Height: 37.5 mm | Storage relative humidity (H-H): 10 - 90% | Quantity per pack: 1 pc(s) | Antenna gain level (max): 4 dBi | Maximum data transfer rate (5 GHz): 1200 Mbit/s | Wi-Fi Multimedia (WMM)/(WME): Yes | Band steering: Yes | MIMO type: Multi User MIMO | Output current: 1.5 A | Master (outer) case width: 315 mm | MIMO: Yes | Product colour: White | Antenna type: Internal | 5 GHz: Yes | AC input voltage: 100 - 240 V | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 1000 Mbit/s | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.11ax | Networking standards: IEEE 802.11g | Networking standards:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

IEEE 802.11n | 2.4 GHz: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.11ac |  
Maximum data transfer rate: 1775 Mbit/s | AC input frequency: 50 - 60 Hz | Networking standards:  
IEEE 802.11b | Weight: 290 g | Ethernet LAN (RJ-45) ports: 1 | Security algorithms: WPA2 | Security  
algorithms: WPA | Operating temperature (T-T): 0 - 50 °C | Storage temperature (T-T): -40 - 70 °C |  
AC adapter included: Yes | Mounting kit: Yes | Security algorithms: WPA3 | Power over Ethernet  
(PoE): Yes | Input current: 0.3 A

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950