

TP-Link Omada ES208G network switch Managed L2 Gigabit Ethernet (10/100/1000) Black



Model: ES208G

Manufacturer: TP-LINK

EAN: 1210002600668

Product Code: 200941

R852

MAC address table: 8000 entries | Auto-negotiation: Yes | Jumbo frames support: Yes | Stackable: No | Virtual LAN features: Tagged VLAN | Power over Ethernet (PoE): No | Forwarding rate: 11.9 Mpps | User guide: Yes | Switching capacity: 16 Gbit/s | Number of VLANs: 32 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | 10G support: No | Product colour: Black | Flow control support: Yes | Operating temperature (T-T): -5 - 45 °C | DC input voltage: 5 V | Height: 25.4 mm | Operating relative humidity (H-H): 10 - 90% | Port mirroring: Yes | VLAN support: Yes | Flash memory: 64 MB | Basic switching RJ-45 Ethernet ports quantity: 8 | Storage relative humidity (H-H): 5 - 90% | Web-based management: Yes | Networking standards: IEEE 802.1ab | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Switch layer: L2 | Networking standards: IEEE 802.3ab |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3i | Depth: 100.7 mm | Virtual LAN features: Port-based VLAN | Auto MDI/MDI-X: Yes | Packet buffer memory: 4 MB | DHCP features: DHCP client | Surge protection: Yes | Store-and-forward: Yes | Link aggregation: Yes | Surge protection voltage: 6 kV | Cloud-managed: Yes | Input current: 0.6 A | Wall mountable: Yes | Jumbo frames: 15000 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | LED indicators: Yes | Width: 158 mm | Power source: DC | IGMP snooping: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Package type: Box | Power supply included: Yes | Fanless: Yes | Rack mounting: No | AC adapter included: Yes | Virtual LAN features: MTU VLAN | Power consumption (max): 2.7 W | Firmware upgradeable: Yes | Gigabit Ethernet (copper) ports quantity: 8 | Loop protection: Yes | Mean time between failures (MTBF): 1141726 h | Heat dissipation: 9.09 BTU/h | Switch type: Managed | Fast leave: Yes | Zero Touch Provisioning (ZTP): Yes | Unified static configuration: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950