

## **TP-Link Omada ES228GMP network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black**



Model: ES228GMP

Manufacturer: TP-LINK

EAN: 1210002600989

Product Code: 200942

## **R7,239**

Certification: FCC, CE, RoHS | Fast leave: Yes | Unified static configuration: Yes | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1ab | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3u | Product colour: Black | Web-based management: Yes | Firmware

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

upgradeable: Yes | Operating temperature (T-T): -5 - 45 °C | Networking standards: IEEE 802.3z | Operating relative humidity (H-H): 10 - 90% | AC input frequency: 50/60 Hz | Ethernet LAN data rates: 10,100,1000 Mbit/s | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power consumption (max): 454.8 W | LED indicators: Yes | Noise level: 46.2 dB | Quick start guide: Yes | AC input voltage: 100 - 240 V | Networking standards: IEEE 802.3i | Storage relative humidity (H-H): 5 - 90% | Power over Ethernet (PoE): Yes | Flash memory: 64 MB | Switching capacity: 56 Gbit/s | IGMP snooping: Yes | Virtual LAN features: Port-based VLAN | Mean time between failures (MTBF): 224143 h | Heat dissipation: 1546.15 BTU/h | Rack mounting: Yes | DHCP features: DHCP client | Power source: AC | Virtual LAN features: MTU VLAN | Switch layer: L2 | Virtual LAN features: Tagged VLAN | Power over Ethernet (PoE) type supported: PoE+ | Power over Ethernet plus (PoE+) ports quantity: 24 | Forwarding rate: 41.66 Mpps | Multicast support: Yes | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-X | Basic switching RJ-45 Ethernet ports quantity: 26 | Copper ethernet cabling technology: 1000BASE-T | MAC address table: 8000 entries | Copper ethernet cabling technology: 1000BASE-X | VLAN support: Yes | Auto MDI/MDI-X: Yes | Packet buffer memory: 4 MB | Switch type: Managed | Depth: 330 mm | 10G support: No | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Width: 440 mm | Height: 44 mm | Link aggregation: Yes | Number of fans: 2 fan(s) | Port mirroring: Yes | Store-and-forward: Yes | Surge protection: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Housing material: Metal | Gigabit Ethernet (copper) ports quantity: 26 | Broadcast storm control: Yes | Jumbo frames support: Yes | Number of VLANs: 32 | Cables included: AC | Surge protection voltage: 6 kV | Rack mount kit: Yes | SFP module slots quantity: 2 | Jumbo frames: 15000 | Total Power over Ethernet (PoE) budget: 384 W | Manual: Yes | Power supply included: Yes | Fanless: No | Cloud-managed: Yes

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950